

LCD PROJECTOR

UltraPortable

CP-X430W

2500 ANSI Lumens

- Native XGA Resolution
- 9.9 lbs.
- DVI & 2 RGB Inputs
- RGB Output
- Component / Composite / S-video Inputs / DVI Inputs
- Contrast Ratio (350:1)
- HDTV Theater Ready
- FCC class B
- 36 dB (Whisper Mode)
- Manual Zoom / Manual Focus
- Vertical & Horizontal Keystone Correction
- "My Screen" (User Programmable Start-up Screen)



Forget-me-not Features:

- Δ 16:9 mode
- Δ Switchable IR receiver for remote controller
- Δ Reverse image function for ceiling mount
- Δ Color temperature and gamma correction
- Δ Digital zoom and freeze function
- Δ Kensington security slot
- Δ Remote controller with laser pointer and mouse function

Input Terminal



HITACHI
Inspire the Next

CP-X430W Ultra-Portable LCD Projector

Model	CP-X430W
--------------	-----------------

Performance Specifications

Liquid crystal panel structure	0.9" polysilicon active-matrix TFT x 3	
Number of Pixels	786,432 pixels (H1024 x V768)	
Resolution	1024 x 768 color pixels	
Lens	Manual zoom 1:1.3 (F1.74 - 2.1)	
Lamp power consumption	250W UHB	
Average lamp life	2,000 hours	
Brightness	2,500 ANSI lumens (2,000 ANSI lumens in Whisper Mode)	
Contrast ratio	350 : 1	
Speakers	1W X 2 Stereo	
Power supply	AC100-120V / AC220-240V 50 / 60HZ	
Power consumption	410W	
Operating temperature	0° - 35° C (32° - 95° F)	
Input signals	RGB	VGA, SVGA, XGA, SXGA (COMPRESSED), MAC 13" , MAC 16"
	VIDEO	NTSC, NTSC4.43, PAL, SECAM, M-PAL, N-PAL, PAL60
	COMPONENT VIDEO	480i, 575i, 480p, 1080i, 720p
Noise level	40 dB (36 dB in Whisper Mode)	

Interface Connectors

RGB input	ANALOG RGB	15-Pin D-sub shrink x 2
	AUDIO	Mini-jack x 2
	DIGITAL RGB	DVI X 1
Video input	S-VIDEO	Mini-Din 4 pin x 1
	COMPOSITE	RCA jack x 1
	COMPONENT	RCA jack x 3
	AUDIO	RCA jack x 2
Audio output	ANALOG RGB	Stereo mini jack x 1
Control terminals	15 Pin D-sub shrink x 1, RS-232C (. serial)	
USB	Remote control mouse	

Chassis

Dimensions	14.2" x 4.2" x 10.1" (W x H x D)
Weight	9.9 lbs.

Supplied Accessories

Wireless remote control with laser pointer (AA batteries), PS / 2 mouse cable, batteries, power cord (U.S., UK, Euro), RCA component cable, RGB cable, multiple language operator / safety manual, handle strip and soft carry case

Screen Size (inches) <i>Diagonal</i>	Min. (a)	Max. (a)
40	62	82
60	94	123
80	127	164
100	160	205
120	192	246
150	241	308
200	323	411

a: Distance from the LCD projector to the screen
The projection distance shown in the table below are for full size



HITACHI

Hitachi America, Ltd. Computer Division

2000 Sierra Point Parkway, MS:760
Brisbane, CA 94005-1835
Tel (800) 225-1741
Fax (650) 244-7776

Web Site: <http://www.hitachi.com/mmp>
For information on other Hitachi products:
1-800-HITACHI (800-448-2244)

Hitachi Canada, Ltd.

6740 Campobello Road
Mississauga, Ontario L5N 2L8
Tel (905) 821-4545
(800) 906-4482
Fax (905) 814-0848
Web Site: <http://www.hitachi.ca>

Specifications and product offerings are subject to change without notice ©2002
Hitachi America, Ltd. All rights reserved. Printed in US CP-X430W DS.02.02