

LCD PROJECTOR

UltraPortable

CP-S317W

3 SERIES

1600 ANSI Lumens

- Native SVGA Resolution
- Contrast Ratio (400:1)
- 6 lbs.
- 2 RGB Inputs
- RGB Output
- Component/Composite/S-video Inputs
- HDTV Theater Ready
- FCC Class B
- 33 dB (Whisper Mode)
- Manual Zoom/Manual Focus
- Vertical & Horizontal Keystone Correction
- Wireless Remote Controller
- "My Screen" (User Programmable Start-up Screen)



Forget-me-not Features:

- Δ 16:9 mode
- Δ Reverse image function for ceiling mount
- Δ Color correction
- Δ Digital zoom and freeze function
- Δ Wide-angle lens
- Δ Kensington slot

Input Terminal



HITACHI
Inspire the Next

CP-S317W Ultra-Portable LCD Projector

Model	CP-S317W
--------------	-----------------

Performance Specifications

Liquid crystal panel structure	0.7" polysilicon active-matrix TFT x 3
Number of Pixels	480,000 pixels
Resolution	800 x 600 color pixels
Colors	16.7 million colors
Aspect ratio	Native 4:3/16:9 compatible
Lens	F1.7 - 1.9 Manual zoom 1:1.2 manual focus
Throw ratio (distance:width)	1.46 : 1 ~ 1.79 : 1
Lamp	150W UHB 2,000 hours
Brightness	1,600 ANSI lumens (Approximately 1,200 ANSI lumens in whisper mode)
Contrast ratio	400 : 1
Speakers	1W x 1
Power supply	AC100-120V/AC220-240V 50/60Hz
Power consumption	240W
Operating temperature	32° - 95° F
Input signals	VGA, SVGA, XGA (COMPRESSED), Mac13", MAC16", NTSC, NTSC 4.43, PAL, M-PAL, N-PAL, PAL60, SECAM, HDTV (480i, 575i, 480p, 1080i, 720p)
Noise level	37dB (33dB in whisper mode)
H Sync	15kHz - 78kHz
V Sync	50Hz - 120Hz

Interface Connectors

RGB input	Standard	15-pin D-sub shrink x 2
RGB output	RGB	15-pin D-sub shrink x1
Video input	S-Video	Mini Din 4-pin terminal x 1
	Composite	RCA jack x 1
	Component	RCA jack x 3
Control terminals	Audio	RCA jack x 2 (L/R)
		15 pin D-sub shrink x 1
USB		Remote control mouse

Chassis

(W x H x D)	11.6" x 3.0" x 9.1"
Weight	6 lbs.


Supplied Accessories

Wireless remote control (AA batteries), Batteries, Power cord (U.S., UK, Euro), RCA video/audio cable, RGB cable, Multiple language operator / safety manual, Handle strip and Carry case

Screen Size 4:3		Throw distance		b inches
Diagonal	Width	Min	Max	
40	32	47	55	1
60	48	71	87	2
80	64	95	114	2
100	80	118	142	3
120	96	142	173	3
150	120	181	217	4
200	160	240	287	6

Throw ratio: 1.46-1.79:1 (distance:width)

- a:** Distance from LCD projector to the screen
b: Distance from the lens center to the bottom of the screen
 The projection distance shown in the table are for full size



HITACHI

Hitachi America, Ltd.
Digital Media Division
 2000 Sierra Point Parkway, MS:760
 Brisbane, CA 94005-1835
 Tel (800) 225-1741
 Fax (650) 244-7776

Web Site: <http://www.hitachi.com/digitalmedia>
 For information on other Hitachi products:
 1-800-HITACHI (800-448-2244)

Hitachi Canada, Ltd.
 6740 Campobello Road
 Mississauga, Ontario L5N 2L8
 Tel (905) 821-4545
 (800) 906-4482
 Fax (905) 814-0848
 Web Site: <http://www.hitachi.ca>

Specifications and product offerings are subject to change without notice ©2002 Hitachi America, Ltd. All rights reserved. Printed in US CP-S317W DS.09.02