

# LCD PROJECTOR

## UltraPortable

# CP-X327W

3 SERIES

1800 ANSI Lumens

- Native XGA Resolution
- Contrast Ratio (350:1)
- 6 lbs.
- 2 RGB Inputs
- RGB Output
- Component/Composite/S-video Inputs
- HDTV Theater Ready
- FCC Class B
- 33 dB (Whisper Mode)
- Manual Zoom/Manual Focus
- Vertical & Horizontal Keystone Correction
- Wireless Remote Controller
- "My Screen" (User Programmable Start-up Screen)



### Forget-me-not Features:

- Δ 16:9 mode
- Δ Reverse image function for ceiling mount
- Δ Color correction
- Δ Digital zoom and freeze function
- Δ Wide-angle lens
- Δ Kensington slot

### Input Terminal



**HITACHI**  
Inspire the Next

# CP-X327W Ultra-Portable LCD Projector

<b>Model</b>	<b>CP-X327W</b>
--------------	-----------------

## Performance Specifications

Liquid crystal panel structure	0.7" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	1,024 x 768 color pixels
Colors	16.7 million colors
Aspect ratio	Native 4:3/16:9 compatible
Lens	Manual zoom 1:1.2 (F1.7 - 1.9), manual focus
Throw ratio (distance:width)	1.46 : 1 ~ 1.79 : 1
Lamp	150W UHB 2,000 hours
Brightness	1,800 ANSI lumens (Approximately 1,440 ANSI lumens in whisper mode)
Contrast ratio	350 : 1
Speakers	1W x 1
Power supply	AC100-120V/AC220-240V 50/60HZ
Power consumption	240W
Operating temperature	32° - 95° F
Input signals	VGA, S-VGA, XGA S-XGA(COMPRESSED), MAC13", MAC16", NTSC, NTSC 4.43, PAL, M-PAL, N-PAL, PAL60, SECAM, S-Video, HDTV (480i, 575i, 480p, 1080i, 720p)
Noise level	39dB (33dB in whisper mode)
H Sync	15kHz - 78kHz
V Sync	50Hz - 120Hz

## Interface Connectors

RGB input	Standard	15-pin D-sub shrink x 2
RGB output	RGB	15-pin D-sub shrink x1
Video input	S-Video	Mini Din 4-pin terminal x 1
	Composite	RCA jack x 1
	Component	RCA jack x 3
	Audio	RCA jack x 2 (L/R)
Control terminals		15-pin D-sub shrink x 1
USB		Remote control mouse

## Chassis

(W x H x D)	11.6" x 3.0" x 9.1"
Weight	6 lbs.
Approvals	UL, C-UL, FCC Class-B, CE, TUV


## Supplied Accessories

Wireless remote control ( AA batteries ), Batteries, Power cord ( U.S., UK, Euro ), RCA video/audio cable, RGB cable, Multiple language operator / safety manual, Handle strip and Carry case

Screen Size 4:3		Throw distance		b inches
Diagonal	Width	Min	Max	
40	32	47	55	1
60	48	71	87	2
80	64	95	114	2
100	80	118	142	3
120	96	142	173	3
150	120	181	217	4
200	160	240	287	6

Throw ratio: 1.46-1.79:1 (distance:width)

**a:** Distance from LCD projector to the screen  
**b:** Distance from the lens center to the bottom of the screen  
 The projection distance shown in the table are for full size



# HITACHI

**Hitachi America, Ltd.**  
**Digital Media Division**  
 2000 Sierra Point Parkway, MS:760  
 Brisbane, CA 94005-1835  
 Tel (800) 225-1741  
 Fax (650) 244-7776

Web Site: <http://www.hitachi.com/digitalmedia>  
 For information on other Hitachi products:  
 1-800-HITACHI (800-448-2244)

**Hitachi Canada, Ltd.**  
 6740 Campobello Road  
 Mississauga, Ontario L5N 2L8  
 Tel (905) 821-4545  
 (800) 906-4482  
 Fax (905) 814-0848  
 Web Site: <http://www.hitachi.ca>

Specifications and product offerings are subject to change without notice ©2002 Hitachi America, Ltd. All rights reserved. Printed in US CP-X327W DS.09.02