

Panasonic®

PT-L520U

Ultra-Portable SVGA Projector—
Powerful, Easy to Use

Performance and Ease of Use

- ✓ One-Touch Auto Setup with digital keystone correction
- ✓ Extra short-throw lens—80-inch diagonal images from approx. 8 feet away
- ✓ Bright 2000 ANSI lumens and 3000-hour lamp life (in low power mode)



PT-L520U Ultra-Portable SVGA Projector — Powerful, Easy to Use

Panasonic's PT-L520U SVGA projector is a great choice for presentations in a wide range of environments. Small, sleek, and ultra-portable, the PT-L520U gives you high brightness, the top performance in its class, and a host of advanced features. Best of all, it's remarkably easy to use.

If you want a projector that stands out for both brightness and performance, check out the PT-L520U. And see just how easy a presentation can be.

Bright 2000 ANSI Lumens, High 300:1 Contrast Ratio

The PT-L520U delivers super-bright performance with 2000 ANSI lumens thanks to a newly-designed, high-performance optical system and high-efficiency 220-W UHM™ lamp. The high contrast ratio of 300:1 ensures that images are sharp, crisp, and easy to see. Both models also provide excellent brightness uniformity of 90%.

Excellent Color Rendition

The use of advanced **10-bit digital gamma correction** circuitry with the latest algorithm gives the PT-L520U naturally vivid, uniform colors and smooth image gradation. Plus, full compatibility with the **sRGB** standard for color space adds more accurate color reproduction to your presentations. The PT-L520U also delivers outstanding moving pictures thanks to a **Digital Cinema Reality (DCR)** circuit and **3-dimensional comb filter***.

* For NTSC signals only

One-Touch Auto Setup

The One-Touch Auto Setup function with digital keystone correction saves adjustment hassles. Panasonic's original, built-in gravity sensor determines the projector's angle relative to the floor and corrects for keystone distortion accordingly. This makes set-up super-easy: Just aim the projector at the screen and press the Auto Setup button. The projector handles all picture adjustments, from phasing and dot clocks to vertical and horizontal position.


Extra Short-Throw Lens

The PT-L520U is equipped with a large-diameter, extra short-throw lens that shortens the necessary projection distance. The shorter projection distance of the PT-L520U saves space. For instance, 2.4 m (8 feet) or less is needed to project an 80-inch diagonal screen, allowing the projector to be placed at the front of the table. This convenient feature enables comfortable presentations with large, easy-to-see images even in small rooms.

Accepts Up to Two RGB Inputs and One RGB Output

Two RGB inputs eliminate the need to re-connect equipment when giving two different presentations back to back. The RGB2

terminal can also serve as a loop-through monitoring terminal for the RGB1 input. For instance, an instructor in a classroom can use this to give a presentation on a large screen while following the same images on a PC, eliminating the need to keep looking at the screen behind. Plus, images can still be monitored on the computer display while the projector is switched to standby mode



Other Important Features

- RGB1 accepts component (YPbPr) video signal
- 3000-hour lamp life in low lamp power mode
- Color temperature selection (standard/high/low)
- Image mode selection (standard/dynamic/natural)
- Full compatibility with sRGB color management (in natural mode)
- HDTV compatibility
- 3x digital zoom
- Freeze function
- Advanced shutter function for image muting
- Selectable 7-language on-screen menu

(English, German, French, Spanish, Italian, Japanese, Chinese)

- VGA expansion on/off selectable
- Video expansion on/off selectable
- Ceiling mountable (option)

Specifications

Native Resolution:	SVGA (800 x 600 pixels)
Brightness:	2000 ANSI lumens
Dimensions (W x H x D):	245 x 118 x 341 mm (9-5/8" x 4-5/8" x 13-4/16")
Weight:	3.9 kg/8.6 lbs
Contrast Ratio:	300:1
Display Technology:	LCD (0.9" polysilicon panels) 480,000 (800 x 600) x 3 AC 220 W UHM™ lamp 3000 hours (in low lamp power mode) 2000 hours (in high lamp power mode)
Lamp:	
Lamp Life:	
Brightness Uniformity:	90%
Keystone Correction:	Digital, vertically adjustable (optically fixed)
Lens Shift:	9:1 (fixed)
Installation:	Ceiling/desk, front/rear (menu selection)
Audio:	2 W (mono)
Input Sources:	Computer (D-sub HD 15-pin x 2); Component video (D-sub HD 15-pin x 1); Composite video (RCA x 1); S-Video (Mini DIN 4-pin x 1); Audio line in for computer (mini x 1); Audio line in for video (RCA, L/R); USB mouse
Output Sources:	VGA monitor out (D-sub HD 15-pin); Audio monitor out (mini x 1)
Computer Compatibility:	VGA, SVGA, XGA, SXGA, Mac PAL, PAL-M, PAL-N, PAL60, SECAM, NTSC, M-NTSC, YPbPr (525i/480i, 625i/576i, 525p/480p, 750p/720p, 1125i/1080i)
Video Compatibility:	
Number of Colors:	Full color (16.7 million)
Aspect Ratio:	4:3 (16:9 compatible)
H-Sync/V-Sync Range:	31–70 kHz, 50–85 Hz
Lens:	Manual zoom/focus lens (1:1–1:1.3), F 1.75, f 28.7–36.0 mm
Image Size (Diagonal):	40"–300" (1.0–7.6 m)
Control:	RS-232C (D-sub 9-pin)
Power Supply:	100–240 V AC (auto-voltage), 50/60 Hz
Power Consumption:	300 W
Operating Temperature:	0°–40°C (32°–104°F)
Operating Humidity:	20%–80%
Safety Regulations:	UL1950, C-UL, FCC class B, EN60950/ IEC60950, EN55024, N55022 (B), EN61000-3-2, EN61000-3-3, VDE, GOST, MIC, CB, C-tick

Panasonic

Panasonic is the brandname of Matsushita Electric.

Panasonic Broadcast & Television Systems Company
Presentation Systems Group
(800) 528-8601
www.panasonic.com/projectors

Headquarters
1 Panasonic Way, 4E-7
Secaucus, NJ 07094
(201) 348-7621

Canada
Panasonic Canada Inc.
5770 Ambler Drive
Mississauga, Ontario
Canada L4W 2T3
(416) 624-5010

Weights and dimensions shown are approximate. Specifications subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. UHM is a trademark of Matsushita Electric Industrial Co., Ltd. VGA and XGA are trademarks of International Business Machines Corporation. Mac is a registered trademark of Apple Computer, Inc. SVGA is a registered trademark of the Video Electronics Standards Association. Windows is a registered trademark of Microsoft Corporation. All other trademarks are the property of their respective trademark owners. Projection images simulated.

PT-L520U1-02JUN100K Printed in Japan.