

Panasonic

Portable Projector

PT-L750U

Brilliant
Performance
Every Time



- 2500 ANSI lumens
- XGA native resolution
- 350:1 contrast ratio
- Under 13 lbs.
- AV / digital terminals
- Optional lenses
- RGB inputs with loop-through monitoring
- Control panel lock
- Easy lamp replacement
- One-touch auto setup
- Keystone correction
- Super quiet (35dB)
- HDTV compatible
- 3D Digital comb filter
- Digital Cinema Reality™
- sRGB compatibility
- Power zoom / focus



Panasonic ideas for life

The Right Choice

The Panasonic PT-750U affords large projector features in a small, portable, whisper quiet (only 35dB) package. At only 12.8 pounds, this little dynamo delivers striking images to front or rear-screen displays in office environments, classrooms, churches, meeting rooms, retail space and other mid-size venues.

Projectors should bring life into any presentation and this one does it with an impressive 2500 ANSI

lumens. Crystal clear XGA resolution and 350:1 contrast ratio round out the equation for audience-pleasing results. And the PT-750U is HDTV-ready with its advanced proprietary video processing chips. We've also included a high-performance 3D digital comb filter and Digital Cinema Reality™ circuits to improve screening quality from composite video and film-based video sources. And its sRGB compatibility ensures proper color representation across a wide variety of digital products.

The Projection Connection

An array of AV, digital and control ports allow for easy connectivity with video and computer sources such as VCRs, camcorders, DVD players, digital cameras, and even control systems. The PT-L750U also features dual RGB inputs with "monitor out," making it perfect for academic applications.

Features and Value

The PT-L750U keeps it simple, yet flexible when it comes to installation and integration. For example, a clever cable cover centers the



Cable cover

lens and secures the cabling. Initial installation is easy thanks to one-touch auto set-up, advanced vertical and horizontal keystone correction, and powered zoom and focus.


We also offer a variety of optional lenses so you can dial in the perfect image, every time.

The PT-L750. Simply brilliant.



The One-Touch Auto Setup features a built-in gravity sensor plus digital keystone correction.


PT-L750U Specifications			Supplied Accessories		
Native Resolution.....XGA 1024 x 768	Video.....NTSC, M-NTSC, PAL, PAL-M, PAL-N, PAL60, SECAM, YPbPr (480i/525i, 625i/PAL60, 480p/525p, 720p/750p, 1080i/1125i)	AUDIO IN.....M3 (L, R) x 1 (common for DVI-D, RGB1, RGB2 and RGB3 inputs)	Power cord	Battery for RC	Instructional Manual
Brightness.....2500 ANSI lumens (with supplied lens)	Optical Axis Shift.....10.0 (fixed)	VIDEO IN.....RCA x 1	Full-function remote control w/laser pointer	RGB cable	Warranty card
Display Technology.....LCD 1.0" diagonal with Micro Lens Array Pixels: 786,432 (1,024 x 768) x 3 (total of 2,359,296)	Digital Keystone Correction.....Vertical: ±35° with no horizontal correction* Horizontal: ±7° with no vertical correction* *With supplied lens. Correction range differs when both vertical and horizontal keystone distortions are corrected at the same time. This also differs depending on input signal.	S-VIDEO IN.....Mini DIN 4-pin x 1		AV cable	Lens cap
Contrast Ratio.....350:1	Installation.....Ceiling/desk, front/rear (menu selection)	AUDIO OUT.....M3 (L, R) x 1		Cable cover	
Lens.....Powered zoom/focus (1:1-1:1.3), F 1.7-2.1, f 40.7- 52.8 mm	Audio.....2 x 2.0 W	SERIAL.....D-sub 9-pin (female) x 1 for external controller (RS-232C)	Optional Accessories		
Lamp.....270 W UHM lamp / 2000 hours (low lamp power mode)	Terminals: DVI-D IN.....DVI-D 24-pin x 1 RGB1 IN.....D-sub HD 15-pin x 1 RGB2 IN/RGB OUT.....D-sub HD 15-pin x 1 (Selectable with on-screen menu. Serves as RGB1 output, or RGB3 output.) RGB3 IN.....5-BNC x 1	REMOTE IN.....D-sub 9-pin (female) x 1 for external controller	Replacement lamp	ET-LA780	
Projection Size.....40-300 inches/1,016-7,620mm diagonally (4:3 aspect ratio)		USB MOUSE.....4-pin B-type x 1, for wireless remote mouse control	High ceiling mount bracket	ET-PK780	
Colors.....Full color (16.7 million colors)		Dimensions.....11-7/16" (W) x 5-3/8" (H) x 16" (D) 290mm (W) x 137mm (H) x 406 mm (D) (Dimensions w/terminal cover detached.)	Low ceiling mount bracket	ET-PK780S	
Center-to-Corner Uniformity Ratio.....90%		Weight.....12.8 lbs / 5.8 kg	1.3 to 1.7:1 zoom lens*	ET-LE10	
H-Synch Range.....15-91 kHz		Power Supply.....100V ~ 240V, 50/60 Hz	2.6 to 4.2:1 zoom lens*	ET-LE20	
V-Synch Range.....56-87 Hz		Power.....380 W (during standby mode with fan stopped: Max. 3.5 W)	4.0 to 5.6:1 zoom lens*	ET-LE30	
Computer.....VGA, SVGA, XGA, SXGA, UXGA, Mac Compatibility		Consumption.....380 W (during standby mode with fan stopped: Max. 3.5 W)	Wireless USB mouse receiver	ET-RMRC1	
		Operating Temp.....32°-104°F (0° - 40°C)	DVI-D cable	ET-SCDV03	
		Audible noise.....35 dB (low lamp power mode)	* user replaceable		



I M A G E S I Z E S / P R O J E C T I O N D I S T A N C E S									
Lens Description Model Number	1.3 to 1.7:1 Short Throw ET-LE10 — Optional		1.9 to 2.6:1 Standard Throw Supplied		2.6 to 4.2:1 Medium Throw ET-LE20 — Optional		4.0 to 5.6:1 Long Throw ET-LE30 — Optional		
Diagonal Image	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	
40" / 3.3' / 1.0m"	3.6' / 1.1m	4.3' / 1.3m	5.2' / 1.6m	6.6' / 2.0m	6.9' / 2.1m	10.8' / 3.3m	11.2' / 3.4m	15.1' / 4.6m	
60" / 5.0' / 1.5m"	5.2' / 1.6m	6.6' / 2.0m	7.9' / 2.4m	10.2' / 3.1m	10.5' / 3.2m	16.4' / 5.0m	16.4' / 5.0m	22.6' / 6.9m	
80" / 6.7' / 2.0m"	7.2' / 2.2m	8.9' / 2.7m	10.5' / 3.2m	13.8' / 4.2m	14.1' / 4.3m	22.3' / 6.8m	21.7' / 6.6m	30.2' / 9.2m	
100" / 8.3' / 2.5m"	8.9' / 2.7m	11.5' / 3.5m	13.1' / 4.0m	17.4' / 5.3m	17.7' / 5.4m	27.9' / 8.5m	26.9' / 8.2m	37.7' / 11.5m	
150" / 12.5' / 3.8m"	13.1' / 4.0m	17.1' / 5.2m	20.0' / 6.1m	25.9' / 7.9m	26.9' / 8.2m	42.3' / 12.9m	40.4' / 12.3m	56.8' / 17.3m	
200" / 16.7' / 5.1m"	17.7' / 5.4	23.0' / 7m	26.6' / 8.1m	34.8' / 10.6m	36.1' / 11.0m	56.4' / 17.2m	53.5' / 16.3m	75.5' / 23.0m	
250" / 20.8' / 6.4m"	22.0' / 6.7m	28.9' / 8.8m	33.1' / 10.1m	43.6' / 13.3m	45.3' / 13.8m	70.9' / 21.6m	66.9' / 20.4m	94.2' / 28.7m	
300" / 25.0' / 7.6m"	26.6' / 8.1m	34.8' / 10.6m	40.0' / 12.2m	52.5' / 16.0m	54.1' / 16.5m	85.3' / 26.0m	80.1' / 24.4m	113.2' / 34.5m	

*Image sizes and distances are approximate.

Lens-aligned mounting brackets for both high or low ceilings are available as optional accessories



Panasonic is the brandname of Matsushita Electric

Panasonic Broadcast & Television Systems Company
Presentation Systems Group
800 528 8601
www.panasonic.com/projectors

Headquarters

1 Panasonic Way, 4E-7
Secaucus, NJ 07094
201 348 5300

Panasonic Canada Inc.

5770 Ambler Drive
Mississauga, Ontario
Canada L4W 2T3
416 624 5010

Weights and dimensions shown are approximate. Specifications subject to change without notice. This product may be subject to export control regulations. UHM is a trademark of Matsushita Electric Industrial Co., Ltd. VGA and XGA are trademarks of International Business Machines Corporation. Mac is a registered trademark of Apple Computer, Inc. SVGA is a registered trademark of the Video Electronics Standards Association. Windows is a registered trademark of Microsoft Corporation. All other trademarks are the property of their respective trademark owners. Projection images simulated.

PT-L750U 02Sept30K Printed in the U.S.A.

Please contact Panasonic or your dealer for a demonstration.

Panasonic ideas for life