

DP6155



QUIET OPERATION

Less than 34dB, for whisper-quiet operation

LIGHTWEIGHT FLEXIBILITY

At 7.5 lbs (3.4 kg) it easily moves from room to room

MULTIPLE INPUTS

Connect up to five different sources simultaneously with single-button transitions between media sources

EXCEPTIONAL IMAGES

450:1 contrast ratio coupled with native XGA resolution display detailed images with clarity

HIGH BRIGHTNESS

2000 ANSI lumens for clear, vibrant images that will dazzle your audience

DIGITAL VISUAL INTERFACE (DVI)



Allows pure digital connectivity for emerging standards; two additional analog computer inputs support analog connections

proxima[®]

InFocus Professional Series

DP6155

flexibility, affordability and versatility



Simultaneously connect three computer sources to accommodate multiple presenters

Adjust the manual zoom and focus for large, vibrant images

SET UP

Supports two composite and S-Video sources such as a DVD player or a VCR to project video with stereo audio

TECHNICAL SPECIFICATIONS

Native Resolution	· XGA (1024 x 768)
Display Technology	· 3 x .9" polysilicon LCDs with MLA (Micro Lens Array)
Input Sources	· 3 computer, 1 S-Video, 1 composite video, 1 video audio, 1 USB mouse, 1 PS/2 mouse, 1 RS-232
Output Sources	· 1 monitor (VGA 15-pin HDDSUB), 1 audio (2 x RCA L/R), wired remote (2.5 mm mini-jack)
Computer Compatibility	· IBM PC or compatibles, Apple Macintosh with video outputs
Video Compatibility	· S-Video, composite video, PAL, PAL-M, PAL-N, SECAM, NTSC 3.58/4.43
Brightness	· 2000 ANSI lumens
Brightness Uniformity	· Greater than 75%
Contrast Ratio	· 450:1 full on/full off
Number of Colors	· 16.7 million
H-Sync Range	· 15 - 100 kHz
V-Sync Range	· 43 - 130 Hz
Dot Clock	· 160 MHz analog; 112 MHz digital
Digital Keystone Correction	· ±15° adjustable
Projection Lens	· f = 36 - 47 mm · F/1.8 - 2.1 · 1.3:1 Manual zoom and focus
Throw Ratio	· 1.9 - 2.5:1 (distance:width)
Minimum Projection Distance (from screen)	· 1.3 m - 10 m
Aspect Ratio	· Std: 4:3 - wide: 16:9
Image Size (diagonal)	· 20" - 260" (580 mm - 6604 mm)
Projection Methods	· Front, rear, ceiling
Audio	· 2 x 1 Watt stereo
Control	· Via on-board menu or remote control
Communication	· RS-232 Serial
Lamp	· 200 Watt UHP
Lamp Life	· 2000 hours
Dimensions (with lens)	· 9.8" (W) x 3.9" (H) x 12.6" (L) · 249 mm (W) x 98 mm (H) x 320 mm (L)
Weight	· 7.5 lbs (3.4 kg)
Power Consumption	· Greater than 220 Watts
Power Supply	· 100V - 240V at 50 - 60 Hz
Operating Temperature	· 50° - 95° F (10° - 35°C)
Menu Languages	· English, French, Spanish, Italian, Portuguese, German, Norwegian, Dutch, simplified Chinese, traditional Chinese, Japanese
Audible Noise	· Less than 34dB
Approvals	· CE, UL, cUL, FCC Class A
Lamp Warranty	· 90 days or 500 hours
Warranty	· Two years on parts and labor. · One year ProXchange (available in U.S., Canada, EU Countries, Norway, Switzerland)

FEATURES

The digital DP6155 offers unsurpassed data connectivity with Digital Visual Interface (DVI) connectivity for exceptional performance in any environment. This feature-packed projector makes projecting in small conference rooms a snap. Its quiet operation, high brightness, XGA resolution, digital keystone correction, weight and high contrast ratio make it the perfect solution for those who need flexibility and outstanding performance.

- Quiet operation – at less than 34dB it minimizes distractions and maximizes audience interaction
- High brightness – at 2000 ANSI lumens and XGA resolution, images are clear and detailed in ambient room lighting
- Unsurpassed DVI connectivity, with zoom and focus adjustments, and digital keystone correction make the DP6155 flexible in any environment
- Multiple video and data inputs allow for seamless switching between presenters and media sources
- Intuitive on-screen menu available in 10 languages
- 2,000 hour lamp life yields lower cost of ownership
- Monitor loop-through feature enables the user to face their audience and see their presentation on-screen
- Simplified set-up and ease-of-use features make the DP6155 easy to move from room to room, which stretches budget dollars

Model DP6155 Ships With:

- **BatMouse III remote control with batteries and laser pointer**
- **U.S. and European power cords**
- **Product documentation**
- **VGA cable, DVI digital data cable, audio/video cable, USB mouse cable, mouse cable and adapters for PS/2 and MS serial, audio cable**
- **Soft carrying case**
- **Lens cap**

ORDERING INFORMATION

Model Number	
DP6155	For worldwide use
Optional Accessories	
CASE-183	Shipping Case
CASE-801	Samsonite Deluxe Travel Case
HW-EBEAM	eBeam (Web Enabled Electronic Meeting Assistant
HW-PORTSCR40	Portable Screen 40" Diagonal
HW-PORTSCR50	Portable Screen 50" Diagonal
HW-WALLSCR84	Pull Down Screen 84" Diagonal
HW-RFPOCKTPNT	Pocket Point RF Remote Control w/Laser Pointer (US, Mexico, Canada only)
SP-LOCK PC	Guardian Projector Lock
HW-DLXSCRN	Deluxe Insta-Theater Screen 60" Diagonal
LAMP-031	Replacement Lamp, 2000 hours



PROJECTION DISTANCES/IMAGE SIZES

Projection Distance	Image Size (Diagonal)				Image Size (Horizontal)			
	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
3.60' 1.10m	1.80' 0.55m	2.36' 0.72m	1.44' 0.44m	1.89' 0.58m				
6.56' 2.00m	3.28' 1.00m	4.33' 1.32m	2.62' 0.80m	3.46' 1.06m				
13.12' 4.00m	6.56' 2.00m	8.68' 2.63m	5.25' 1.60m	6.94' 2.10m				
19.68' 6.00m	9.84' 3.00m	12.96' 3.95m	7.87' 2.40m	10.37' 3.16m				
26.24' 8.00m	13.12' 4.00m	17.26' 5.26m	10.50' 3.20m	13.81' 4.21m				
32.80' 10.00m	16.40' 5.00m	21.59' 6.58m	13.12' 4.00m	17.27' 5.26m				

NOTE: Metric conversions are approximate.

www.proxima.com www.infocus.com

InFocus Corporate Headquarters:

In the Americas: 27700B SW Parkway Avenue • Wilsonville, Oregon 97070-9215
Phone: 503-685-8888 • 1-800-294-6400 • Fax: 503-685-8887

In Europe: Olympia 1 • NL-1213 NS Hilversum, The Netherlands
Phone: (31) 35 6474000 • Fax: (31) 35 6423999
Freephone: 008000 4636287 (008000 INFOCUS)

In Asia: 238A Thomson Road • #18-01/04 Novena Square
Singapore 307684 • Telephone: (65) 6334-9005 • Fax: (65) 6333-4525

Proxima is a registered trademark of InFocus Corporation.
Other trademarks are property of their respective owners. ©2001 InFocus Corporation.
All rights reserved. 07/02 815-0003-02 DP6155_DS_E.qxd