



ULTRALIGHT X350

the premium, versatile power house

EXTREME BRIGHTNESS

1100 ANSI lumens

DVI/I DIGITAL CONNECTION

for pure digital or standard VGA connectivity

MODULAR DESIGN

optimized for portability, flexibility, and upgradeability

SILENT OPERATION

at less than 32 dB, it's quieter than the average conversation



TRUE XGA RESOLUTION

adapts directly to any XGA source without image conversion or distortion

SMART ELECTRONICS

AND SOFTWARE

fully-digital, auto-sensing for optimal output in every environment

PROXIMA ULTRALIGHT® X350

Versatility that's truly revolutionary! At 1100 ANSI lumens, the fully-digital, fully-loaded Proxima UltraLight X350 helps you share information and collaborate in any environment. Whisper-quiet operation ensures that your message gets heard, and exceptional connectivity to a laptop, PC, DVD player or VCR provides high performance in any application. And, the X350's modular design offers outstanding flexibility and unbeatable upgrade potential. With an incredible feature set, the X350 works perfectly in conference rooms and its go-anywhere size makes it easy to take on the road. Unique auto-sensing electronics guarantee optimal performance in any setting.

- at 1100 ANSI lumens, it's bright enough in any environment
- at only 3.5 pounds, it offers the utmost in portability, with the smartest digital features
- the X350 offers whisper-quiet operation at less than 32 dB
- XGA (1024 x 768) resolution and DLP™ technology lets you display your most detailed images with clarity
- Digital Visual Interface (DVI/I) allows pure digital connectivity for emerging standards, while also supporting current PCs with analog and USB
- modular design supports future upgrades and video module offers the flexibility to remove the component for the lightest load possible
- video module port replicates DVI/I and USB, in addition to supporting RCA, S-video, and one-watt stereo speaker
- optional Advanced Connectivity module adds component video support and ProjectionLink single-wire connectivity for easy ceiling-mounted installation
- equipped for Kensington® lock hardware to protect the X350 from theft
- comes with 90-day lamp warranty and two years of free ProXchange™ service for overnight projector replacement in the unlikely event that your X350 is in need of repair

FULLY-DIGITAL, SMART ELECTRONICS

- auto source selection
- auto image optimization
- auto Room Light Sensing instantly senses room light conditions and adjusts brightness and contrast for optimized image to preserve lamp life
- thermal adaptive cooling

INTELLIGENT SOFTWARE FOR EASY PROJECTOR CONTROL

- USB port offers control of projector functions and hot mouse connection
- Projector Manager allows source switching, power and screen saver management
- icon-based menu system for simple user interface

X350 TECHNICAL SPECIFICATIONS

Native Resolution	• XGA (1024 x 768)
Resolution Supported	• VGA (640 X 480), SVGA (800 X 600), XGA (1024 X 768), SXGA (1280 X 1024)
Brightness	• 1100 ANSI lumens
Brightness Uniformity	• 80%
Contrast Ratio	• 500:1 (full on/full off)
Computer Compatibility	• IBM or compatibles • Apple Macintosh
Video Compatibility	• PAL BGHI, N, combination N, M, NTSC M, N, 4.43, Japan, SECAM, MESECAM
Display Technology	• Single-chip DLP
Input Sources (base unit)	• Supports DVI, VGA and USB
Input Sources (video module)	• S-video, composite video and audio • DVI, VGA and USB (port replicated from base unit)
Input Sources (advanced connectivity module)*	• Component video, S-video, composite video • DVI, VGA • ProjectionLink UTP
Output Sources (video module)	• Audio
Output Sources (advanced connectivity module)*	• Monitor out (ProjectionLink Transmitter) • RS-232 (ProjectionLink Transmitter)
H-Sync Range	• 15 -100 KHz
V-Sync Range	• 43.5 - 130 Hz
Bandwidth	• 12 -140 MHz
Horizontal Resolution (TV Lines)	• 1024
Keystone Correction (Digital)	• +/- 6 ° Digital /12 ° Optical offset
Projection Lens	• 1.3:1 Zoom Lens
Projection Distance	• 4.3 ft. to 19.7 ft. (1.3 m to 6.0 m)
Aspect Ratio	• 4:3 (Includes some 16:9 support)
Image Size (Diagonal)	• 1.9 ft. to 14.4 ft. (0.6 m to 4.4 m)
Throw Ratio	• 1.71 - 2.86:1
Audio	• 1 Watt speaker in module
Remote Control	• BatMouse IV with laser pointer and mouse support
Lamp (Life)	• 120 Watt (2000 Hours)
Dimensions (H x W x L)	• 2.36 in. x 7.12 in. x 8.42 in. • 60 mm x 181 mm x 214 mm (base unit only)
Weight	• 3.5 lbs. (1.5kg)
Power Consumption	• Operation: < 170 Watts; stand by: < 5 Watts
Power Requirements	• 85-264VAC, 47-63 Hz
Operating Temperature	• 5 - 35° C at sea level • 5 - 30° C 3000 m • 41 - 95° F at sea level • 41 - 86° F 10000 ft.
On-Screen Menu Languages	• English, French, Spanish, Portuguese, German, Italian, Chinese, Japanese, Norwegian
Audible Noise	• <32 dB nominal room conditions
Approvals	• CE, UL, CUL, FCC Class A Subpart J, Part 15
Warranty	• two-years on parts and labor • 90-days (or 500 hours) on lamp • two-years of free ProXchange replacement service

*Optional Accessory

Optional Accessories:

PART XXX	Advanced Connectivity Module
PART XXX	Advanced Connectivity Module—ProjectionLink Bundle

UltraLight X350 Set Up

Position the UltraLight X350 anywhere in the room.



X350 SHIPS STANDARD WITH:

- Remote control with mouse control and laser pointer
- U.S. and European power cords
- Product documentation
- Computer DVI/I to VGA cable, Computer DVI/I to DVI cable, AV cable, S-video cable, USB cable (for mouse control), audio cable — all with color coded connectors for easy set-up
- Projector Manager CD-ROM
- Soft carrying case
- Lens cap

ORDERING INFORMATION

Model Number	
X350	For worldwide use
Optional Accessories	
CASE-801	Samsonite rolling soft carry-on
CASE-802	Samsonite compact carry-on rolling soft case
CASE-182	Compact rolling hard case
CASE-193	Deluxe rolling hard case
A650	50 in. portable tabletop screen
LAMP-027	120-Watt lamp

X350 PROJECTION DISTANCES / IMAGE SIZES

Projection Distance		Image Size (Diagonal)			
		Minimum		Maximum	
4.3'	1.3 m	1.9'	0.6 m	3.1'	1.0 m
6.6'	2.0 m	2.9'	0.9 m	4.8'	1.5 m
9.8'	3.0 m	4.3'	1.3 m	7.2'	2.2 m
13.1'	4.0 m	5.7'	1.7 m	9.6'	2.9 m
16.4'	5.0 m	7.2'	2.2 m	12.0'	3.7 m
19.7'	6.0 m	8.6'	2.6 m	14.4'	4.4 m

PROJECTORS THAT GO

proxima

www.proxima.com
1.800.294.6400

Premium Projectors

ULTRALIGHT X350

proxima

www.proxima.com
www.infocus.com

InFocus Corporation: 27700B SW Parkway Avenue • Wilsonville, Oregon 97070-9215
Phone: 503-685-8888 • 1-800-294-6400 • Fax: 503-685-8887

In Europe: Olympia 1 • NL-1213 NS Hilversum, The Netherlands
Phone: (31) 35 6474000 • Fax: (31) 35 6423999
Freephone: 008000 4636287 (008000 INFOCUS)

In Asia: 238A Thomson Road • #18-01/04 Novena Square
Singapore 307684 • Telephone: (65) 334-9005 • Fax: (65) 334-4525

Proxima and Proxima UltraLight are registered trademarks and ProXchange is a trademark of InFocus Corporation. DLP and Digital Light Processing are trademarks of Texas Instruments. ©2001 InFocus Corporation. All rights reserved. 06/01 709-00862-4 X350 data sheet.qxd