

Full 15-inch Viewable Screen

Active Matrix

Slim Profile and Elegant Design

Plug and Play

Low Power Consumption (Energy Star)

Low to No Radiation Emission

Challenge yourself...



Challenge yourself...



CT1501

Panel	Type	15" viewable diagonal TFT type
	Pixel Pitch	0.297mm (H) × 0.297mm (V)
	Viewing Angle	Horizontal : 160° Vertical : 125°
	Display Area (H x V)	304.128mm × 228.096mm (11.97inch x 8.98inch)
Display Colors		16.7 million (dithering)
Contrast Ratio		300:1 (typical)
Brightness		250 cd/m ² (typical)
Response Time	Rising/Falling	40ms
Scanning Frequency	Horizontal	31-61KHz
	Vertical	56-75Hz
Recommended Resolution		1024 x 768 / 60Hz
Input Signals	VGA	Video RGB Analog, Sync H/V SEPERATE (TTL)
	Compatibility	Windows® 95/98/2000, Mac, Unix, Linux, OS/2 compatibles
User Controls		Brightness, Contrast, Auto-Adjustment, Clock, Phase H/V position, Color Control, 5 OSD Language
I/O Connectors		VGA 15 pin mini D-sub DC Power in
Power		AC 100~240V, 50/60Hz Input
		12V, 3.3A Max DC Output
Power Consumption		25watts (typical)
Power Management		VESA DPMS Compatible
Plug & Play		VESA DDC 1/2B
Temperature	Operation	0°C~50°C (32°F~122°F)
	Storage	-20°C~60°C (-4°F~140°F)
Dimensions	Physical (W x H x D)	384.0mm × 383.5mm × 190.0mm (15.11inch x 15.10inch x 7.48inch)
Weight	Net	3.4kg (7.48lbs)
	Gross	4.8kg (10.56lbs)
Regulations		UL, cUL, CB, TÜV/GS, CE, FCC-B, VCCI, TCO95, MPR II

Copyright © CORNEA Systems, Inc. 2001. All rights reserved.
Windows is a registered trademark of Microsoft Corporation.
The provided information is subject to change without notice.



CORNEA
SYSTEMS, INC.

www.corneasystems.com

Email: sales@corneasystems.com

Phone: (408) 944-9180

Fax: (408) 944-9181

Toll Free: (800) 681-6155