CORNEA
SYSTEMS, INC.

CT1700

Full 17-inch Viewable Screen
Built-in Speakers
Active Matrix
Slim Profile and Elegant Design
Detachable Base
VESA Standard Wall Mount
Plug and Play
Low Power Consumption (Energy Star)
Low to No Radiation Emission

Break the ice...

Break the ice...

CT1700

Panel	Type	17" viewable diagonal TFT type
	Pixel Pitch	0.264mm (H) × 0.264mm (V)
	Viewing Angle	Horizontal : 140°
		Vertical : 110°
	Display Area (H x V)	337.92mm x 270.336mm (13.30inch x 10.64inch)
Display Colors		16.7 million
Contrast Ratio		400:1 (typical)
Brightness		250cd/m^2 (typical)
Response Time	Rising/Falling	25ms
Scanning Frequency	Horizontal	31-82Khz
	Vertical	56-75Hz
Recommended Resolution		1280 x 1024 / 75Hz
Input Signals	VGA	RGB Analog, Stereo Jack In/Out
	Compatibility	Windows® 95/98/2000, Mac, Unix, Linux, OS/2 compatibles
User Controls		Auto-Adjustment, Brightness, Contrast, H/V position, Image control
		Audio control, Color control, 5 OSD Language, Miscellaneous
I/O Connectors		VGA 15 pin mini D-sub, Stereo Audio In/Out
		DC Power in
Power		AC 100~240V, 50/60Hz Input
		12V, 3.3A Max DC Output
Power Consumption		36watts (typical)
Power Management		VESA DPMS Compatible
Plug & Play		VESA DDC 1/2B
Temperature	Operation	0°C~50°C (32°F~122°F)
	Storage	-20°C~60°C (-4°F~140°F)
Dimensions	Physical (W x H x D)	444mm x 452.7mm x 241.4mm (17.48inch x 17.82inch x 9.51inch)
Weight	Net	7.2kg (15.84lbs)
	Gross	10.1kg (22.22lbs)
Regulations		UL, cUL, CE, CB, FCC-B, VCCI, MPR II
Features		Built-in speakers, VESA standard wall mount

CORNEA
SYSTEMS, INC.

www.corneasystems.com

Email: sales@corneasystems.com   Phone: (408) 944-9180   Fax: (408) 944-9181   Toll Free: (800) 681-6155