

Full 18.1 Viewable Screen
Active Matrix
Slim Profile and Elegant Design
Detachable Base
VESA Standard Wall Mount
Built-in Speakers
Plug and Play
Low Power Consumption (Energy Star)
Low to No Radiation Emission

Feel the force...



Feel the force...



CT1810

Panel	Type	18.1" viewable diagonal TFT type
	Pixel Pitch	0.2805mm (H) × 0.2805mm (V)
	Viewing Angle	Horizontal : 160° Vertical : 160°
	Display Area (H x V)	359.2mm x 287.2mm (14.14inch x 11.31inch)
Display Colors		16.7 million
Contrast Ratio		300:1 (typical)
Brightness		200cd/m ² (typical)
Scanning Frequency	Horizontal	20-82Khz
	Vertical	56-85Hz (56-75Hz at 1280 x 1024)
Recommended Resolution		1280 x 1024 / 75Hz
Input Signals	VGA	RGB Analog
	Compatibility	Windows 95, Windows 98, Windows 2000, Mac, Unix, Linux, OS/2 compatibles
User Controls		Auto-Adjustment, Brightness, Contrast, H/V position, Image control, Color control, 5 OSD Language, Miscellaneous
I/O Connectors		VGA 15 pin mini D-sub, Audio in/out DC Power in
Power		AC 100~240V, 50/60Hz Input 12V, 5A Max DC Output
Power Consumption		36watts (typical)
Power Management		VESA DPMS Compatible
Plug & Play		VESA DDC 2B
Temperature	Operation	0°C~40°C (32°F~104°F)
	Storage	-25°C~60°C (-13°F~140°F)
Dimensions	Physical (W x H x D)	444mm x 452.7mm x 241.4mm (17.48inch x 17.82inch x 9.51inch)
Weight	Net	7.9kg (17.38lbs)
	Gross	10.8kg (23.76lbs)
Regulations		UL, cUL, CSA, FCC-B, CE, VCCI
Features		Built-in speakers, VESA standard wall mount



Copyright (C) CORNEA Systems, Inc. 2001. All rights reserved.

CORNEA
SYSTEMS, INC.

www.corneasystems.com

Email: sales@corneasystems.com

Phone: (408) 944-9180

Fax: (408) 944-9181

Toll Free: (800) 681-6155