

Full 17-inch Viewable Screen

Active Matrix

Super Slim Profile and Elegant Design

Plug and Play

Low Power Consumption (Energy Star)

Low to No Radiation Emission

Experience nature...



Experience nature...



MP704

Panel	Type	17" viewable diagonal TFT type
	Pixel Pitch	0.264mm (H) × 0.264mm (V)
	Viewing Angle	Horizontal : 140° Vertical : 110°
	Display Area (H×V)	337.92mm × 270.336mm (13.3inch x 10.64inch)
Display Colors		16.7 million (dithering)
Contrast Ratio		400:1 (typical)
Brightness		250cd/m2 (typical)
Scanning Frequency	Horizontal	31-82Khz
	Vertical	56-75Hz
Recommended Resolution		1280 x 1024 / 75Hz
Input Signals	VGA	RGB Analog
	Compatibility	Windows® 95/98/2000, Mac, Unix, Linux, OS/2 Compatibles
User Control		Auto-Adjustment, Brightness, Contrast, H/V position, Clock, Phase Color Control, 5 OSD Language, Miscellaneous
I/O Connectors		VGA 15 pin mini D-sub DC Power in
Power		AC 100-240V, 50/60Hz Input 12V, 3.3A Max DC Output
Power Consumption		36 Watts (typical)
Power Management		VESA DPMS Compatible
Plug & Play		VESA DDC 1/2B
Temperature	Operation	0°C - 50°C (32°F - 122°F)
	Storage	-20°C - 60°C (-4°F - 140°F)
Dimensions	Physical (W×H×D)	414.0mm × 369mm × 170.5mm (16.30inch x 14.53inch x 6.71inch)
Weight	Net	4.9kg (10.81lbs)
	Gross	6.7kg (14.77lbs)
Regulations		UL, cUL, CE, CB, FCC-B, VCCI, TCO95

Copyright © CORNEA Systems, Inc. 2001. All rights reserved.
Windows is a registered trademark of Microsoft Corporation.
The provided information is subject to change without notice.

