



- 2,000 ANSI Lumens
- Native XGA Resolution
- 6 lbs.
- 16:9 Mode
- Contrast Ratio 350:1
- 2 RGB Inputs/RGB Output
- Component/Composite/S-Video Input
- Reverse image function for ceiling mount
- Vertical & Horizontal Keystone Correction
- My Screen (user programmable start-up screen)
- HDTV Theater Ready
- Remote control
- 33dB (Whisper mode)
- Comes with soft case
- Color correction
- Kensington security slot
- Wide-angle lens
- FCC Class B
- Digital Zoom (x4)
- Picture freeze function
- Manual zoom & manual focus

SPECIFICATIONS

Model name	CP-X328 series		
Liquid crystal panel structure	0.7" polysilicon active-matrix TFT x 3		
Number of pixels	786, 432 pixels (H 1,024 x V 768)		
Resolution	1,024 x 768 color pixels		
Colors	16.7 million colors		
Aspect ratio	Native 4:3/16:9 compatible		
Lens	Manual zoom 1:1.2 (F1.7 - 1.9), manual focus		
Throw ratio (distance:width)	1.47 ~ 1.79 : 1		
Lamp	150W UHB (130W in whisper mode)		
Brightness	2,000 ANSI lumens (1,600 ANSI lumens in whisper mode)		
Expected lamp life	Approx. 2,000 hours (Approx. 4,000 hours in whisper mode)		
Contrast ratio	350 : 1		
Speakers	1W x 1		
Power supply	AC100-120V/AC220-240V 50/60Hz		
Power consumption	240W		
Operating temperature	32°F ~ 95°F		
Input signals	RGB	VGA, SVGA, XGA, SXGA/LXGA (COMPRESSED), MAC13", MAC16"	
	Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60	
	Component video	480i, 575i, 480p, 1,080i, 720p	
Acoustic noise level	38dB (33dB in whisper mode)		
H sync	15kHz ~ 91kHz		
V sync	50Hz ~ 120Hz		
Vertical keystone correction	Digital keystone +/- 15°		
Horizontal keystone correction	Digital keystone +/- 5°		
Approvals	UL, C-UL, FCC Class B		
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2
	RGB output	RGB	15-pin D-sub connector x 1
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
		Component video	RCA jack x 3
Audio	RCA jack x 2 (L/R)		
Control terminals	15-pin D-sub connector x 1		
	USB connector (USB mouse) x 1		
Compatible controls	PS/2, ADB, serial, RS-232C (serial)		
Dimensions	11.6" x 3.0" x 9.1" (W x H x D)		
Weight	6 lbs.		
Supplied accessories	Remote control, batteries (AA), RGB cable, RCA video/audio cable, power cord, USB cable, operator/safety manual, soft case		
Replace-ment Parts	Lamp	CPS317LAMP (Part #: DT00511)	
	Remote Control	(Part #: HL01891)	



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	47	55
60	48	71	87
80	64	95	114
100	80	118	142
120	96	142	173
150	120	181	217
200	160	240	287

Throw ratio: 1.47-1.79:1 (distance:width)

*: Measured in inches

CP-S318/CP-X328 Dimensions (incl.protruding part)

