

# LCD PROJECTOR

## UltraPortable

# CP-S370W

## 2200 ANSI Lumens

- Native SVGA Resolution
- Contrast Ratio ( 350:1 )
- 7 lbs.
- 2 RGB Inputs
- RGB Output
- Component / Composite / S-video Inputs
- HDTV Theater Ready
- FCC class B
- 34 dB ( Whisper Mode )
- Manual Zoom / Manual Focus
- Digital Keystone Correction



### Forget-me-not Features:

- Δ 16:9 mode
- Δ Reverse image function for ceiling mount
- Δ Color temperature and gamma correction
- Δ Digital zoom and freeze function
- Δ Kensington slot

### Input Terminal



# CP-S370W Ultra-Portable LCD Projector

<b>Model</b>	<b>CP-S370W</b>
--------------	-----------------

## Performance Specifications

Liquid crystal panel structure	0.9" polysilicon active-matrix TFT x 3	
Number of pixels	480,000 pixels ( H1024 x V768 )	
Resolution	800 x 600 color pixels	
Lens	Manual zoom 1:1.3 ( F1.74 - 2.08 )	
Lamp power consumption	200W UHB	
Average lamp life	2,000 hours	
Brightness	2,200 ANSI lumens ( 1,760 ANSI lumens in Whisper Mode )	
Contrast ratio	350 : 1 ( ANSI all black / white measurement )	
Speakers	1W X 2 Stereo	
Power supply	AC100-120V / AC220-240V 50 / 60HZ	
Power consumption	310W	
Operating temperature	0° - 35° C ( 32° - 95° F )	
Input signals	RGB	VGA, SVGA, XGA / SXGA ( Compressed ), MAC13" , MAC16"
	VIDEO	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60
	COMPONENT VIDEO	480i, 575i, 480p, 1080i, 720p
Noise level	40 dB ( 34 dB in Whisper Mode )	

## Interface Connectors

RGB input	ANALOG RGB	15-Pin D-sub shrink x 2
	AUDIO	Mini - jack x 2
Video input	S-VIDEO	Mini - Din 4 pin x 1
	COMPOSITE	RCA jack x 1
	COMPONENT	RCA jack x 3
	AUDIO	RCA jack x 2
Audio output	ANALOG RGB	3.5 Stereo mini jack
Control terminals	15 Pin D-sub shrink x 1, RS-232C ( serial )	
USB	For remote control mouse	

## Chassis

Dimensions	11.7" x 3.0" x 8.98" ( W x H x D )
Weight	7 lbs.

## Supplied Accessories

Remote control ( card type with 4 way mouse function ), PS / 2 mouse cable, Batteries, Power cord ( U.S., UK, Euro ), RCA Component cable, RGB cable, Multiple language operator / safety manual, Handle strip and Carry case

## Spare / Optional Accessory Model Names

Lamp	CPX380 LAMP ( or Parts # DT00431 )
Card type remote controller ( 4 way mouse )	HL01444
Full function remote ( Optional )	HL01791

Screen Size (inches) <i>Diagonal</i>	Min. ( a )	Max. ( a )
<b>40</b>	62	86
<b>60</b>	94	128
<b>80</b>	127	164
<b>100</b>	160	205
<b>120</b>	192	246

Throw distance:  
image width (approx.) 2.02:1 (wide) ~ 2.56:1 (tele)

a: Distance from the LCD projector to the screen  
The projection distance shown in the table below are for full size



# HITACHI

**Hitachi America, Ltd.**  
**Computer Division**  
 2000 Sierra Point Parkway, MS:760  
 Brisbane, CA 94005-1835  
 Tel (800) 225-1741  
 Fax (650) 244-7776  
 Web Site: <http://www.hitachi.com/mmp>  
 For information on other Hitachi products:  
 1-800-HITACHI (800-448-2244)

**Hitachi Canada, Ltd.**  
 6740 Campobello Road  
 Mississauga, Ontario L5N 2L8  
 Tel (905) 821-4545  
 (800) 906-4482  
 Fax (905) 814-0848  
 Web Site: <http://www.hitachi.ca>

Specifications and product offerings are subject to change without notice ©2002 Hitachi America, Ltd. All rights reserved. Printed in US CP-S370W DS.03.02