



GT1150 and GT2150

GT Series Projectors For Demanding Environments

3000 ANSI - GT1150

2500 ANSI - GT2150

CRT Replacement

Horizontal and vertical power lens shift

Power zoom and focus

VORTEX Technology™

Eco-Mode™ lamp technology

Double stackable

Network Interface card option

UXGA compatible resolution:
XGA native - GT1150
SXGA native - GT2150

Innovative design, multiple connections, and a full suite of quick-change optional lenses offer installation flexibility, even in demanding environments.

The GT1150 and GT2150 deliver extraordinary brightness, broad compatibility, and unsurpassed quality for fixed installations in conference rooms, CRT replacements, auditoriums, control rooms and other large venue settings. The unique feature set and our exclusive display technologies make the GT1150 and GT2150 the most adaptable projectors of their kind.

Featuring horizontal and vertical power lens shift, power zoom and focus and double stackability, the GT1150 and GT2150 are the benchmark for easy image adjustments. Via the GTs optional IP addressable network interface card, facility managers are provided with remote access and control enabling management of all projectors from one central location. Multiple RGB and DVI inputs and extensive video compatibility with HDTV, S-Video, component, and composite sources give virtually unlimited connectivity combinations. The GT1150 and GT2150 are also equipped with our exclusive VORTEX Technology™, Advanced AccuBlend™, and AutoSense™ technologies for unparalleled image quality and projector performance and ease of use.

The GT Series are covered by NEC Technologies industry-leading service programs. InstaCare® provides projector repair and return within three business days. When overnight isn't fast enough, NEC offers InstaCare XpressSM.

Solutions with Vision

GT1150 and GT2150



Optical

LCD Panel	1.3" p-Si TFT w/ MLA	
Resolution	GT1150: 1024x768 pixels native, up to UXGA with Advanced AccuBlend GT2150: 1366x1024 pixels native, up to UXGA with Advanced AccuBlend (can display 1280x1024 non-scaled)	
Lens	Power Zoom and Power Focus (except GT10RL) GT19ZL F2.0-2.5, f=48.9-63.7mm GT13ZL F2.3-2.8, f=34.5-42.5mm GT10RL F2.3, f=27mm GT24ZL F2.5-3.2 f=64-92.8mm GT34ZL F2.5-3.4, f=92.4-140.6mm	
Lens Shift	GT19ZL lens Vertical ± 0.5, Horizontal ± 0.25	
Light Output	GT1150: 3000 ANSI lumens standard-mode 2400 ANSI lumens Eco-mode	GT2150: 2500 ANSI lumens standard-mode 2000 ANSI lumens Eco-mode
Lamp	250W NSH	
Lamp Life	Eco-mode 2000H Standard-mode 1500H	
Contrast Ratio	350:1	
Image Size	GT19ZL/GT13ZL/GT10RL - 40-300 inches GT24ZL - 60-400 inches GT34ZL - 80-500 inches	
Projection Distance	GT19ZL lens 4.8-48.0ft (1.5m-14.6m) GT10RL lens 2.7-20.0ft (.8m-6.1m) GT13ZL lens 3.5-32.0ft (1.1m-9.8m) GT24ZL lens 7.47-90.35ft (2.3m-27.8m) GT34ZL lens 18.1-173.2ft (5.5m-52.8m)	
Projection Angle	GT19ZL -9 degree (tele)/11.7 degree (wide) GT13ZL -13.3 degree (tele)/16.4 degree (wide) GT24ZL -6.3 degree (tele)/9.0 degree (wide) GT34ZL -4 degree (tele)/6.2 degree (wide)	
Keystone Correction	±30° electronic, for GT2150 non RGB sources ±15°	

Electrical

Inputs	GT1150 and GT2150: 5-BNC, DVI, VIDEO (NTSC, PAL, SECAM, NTSC4.43), S-Video, 2- RGB, YCbCr Component (optional cable), HDTV - 1080i, 720p, 480p, 480i (optional cable), PC Card Slot	
Outputs	GT1150 and GT2150: RGB out, Audio out, PC control, GT2150: DVI-D	
Synchronization Range	GT1150 Horiz-15 to 100 kHz (non-interlaced) Vertical-48 to 120Hz	GT2150 Horiz-15 to 107 kHz (non-interlaced) Vertical-48 to 120Hz
Telecine Detect	3:2 pull down correction (GT2150 only)	
Cabinet Control	Yes	
Panel Lock	Yes	
Video Bandwidth	GT1150: 100MHz; GT2150: 200MHz	
Pixel Clock Freq	GT1150: 102MHz; GT2150: 200MHz	
Screen Trigger	Stereo mini-jack	
Color Reproduction	16.7 million colors simultaneously, Full color	
Horizontal Resolution	NTSC/PAL/NTSC4.43/YCbCr - 550TV lines, SECAM - 350 TV lines, RGB - 1024dots (H) x 768dots (V) (GT1150); 1366dots (H) x 1024dots (V) (GT2150)	
External Control	RS232, IR (AMX/Creston compatibility)	
Sync Compatibility	Separate Sync / Composite Sync / Sync on G	
Built-in Speakers	5Wx2	
Operational Fan Level	GT1150: <34dB Eco-mode, <37dB Standard; GT2150: <37dB Eco-mode, <39dB Standard	
Power Requirements	100-120VAC/200-240VAC, 50/60Hz	
Input Current	GT1150: 3.9A (100-120 VAC), 1.9A (200-240 VAC) GT2150: 4.2A (100-120 VAC), 2.0A (200-240 VAC)	
Power Consumption	GT1150: 380W; GT2150: 420W	

Mechanical

Installation	Orientation: Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear	
Dimensions (WxDxH)	16.84x19.76x8.36, 421x494x209mm	
Net Weight	GT1150: 22 lbs. (10kg) - without lens; GT2150: 28.2 (13kg) without lens	
Environment	Operational Temp. 32° to 95°F / 0° to 35°C Humidity: 20-80% non-condensing Storage: 14° to 122°F / -10 to 50°C	
Regulations	USA UL 1950 Canada	FCC Class B CSA950 (C-UL)
Accessories	Users manual, wired/wireless addressable remote control, power cable, remote cable, signal cable (GT1150 only), registration card	
Warranty	Registered owners receive a 2-year limited parts and labor warranty including InstaCare. InstaCare provides the original owner limited concurrent 3-business day repair/return coverage. Lamp is 6 months or standard mode rated life.	

Product/Accessories

LCDGT1150	GT1150, XGA, 3000 ANSI projector (no lens)
LCDGT1150-19ZL	GT1150, XGA, 3000 ANSI projector (ships with GT19ZL lens)
LCDGT2150	GT2150, SXGA, 2500 ANSI projector (no lens)
LCDGT2150-19ZL	GT2150, SXGA, 2500 ANSI projector (ships with GT19ZL lens)
GT50LP	Replacement lamp
GT10RL	1:1 Short throw lens
GT13ZL	1.3-1.6:1 Short throw zoom lens
GT19ZL	1.8-2.4:1 zoom lens
GT24ZL	2.4-3.4:1 zoom lens
GT34ZL	3.4-5.2:1 zoom lens
GT50CM	Ceiling mount kit
GTFRAME	Frame for flying or stacking
GT50ATA	ATA shipping case
GTRMT	Replacement remote
GT50LAN	Optional network interface card

Specifications subject to change without notice.

Special Features

Eco-Mode Technology	Increase lamp life through light output adjustments
VORTEX Technology	Provides improved color uniformity, depth and detail for data and video images
Advanced AccuBlend Technology	Ensures detailed images when non-native resolution sources are connected to the projector.
AutoSense Technology	Automatic set-up and one touch adjustments for ease of use
Lens Shift	Powered horizontal and vertical
Network Card	Optional network interface card for internet IP access and control
Keystone Correction	± Digital correction
Screen Trigger	Screen trigger controller compatible
Cabinet Control Panel Lock	Lock cabinet control keys to prevent unauthorized access and adjustments



For more information, call (800) NEC-INFO
or visit www.nectech.com/presentationproducts

NEC Technologies and the NEC logos are registered trademarks of NEC Technologies, Inc. All products and technologies mentioned are trademarks or registered trademarks of their respective manufacturers.

NEC Technologies, Inc.
1250 N. Arlington Heights Rd., Suite 500
Itasca, IL 60143-1248
www.nectech.com