

# Panasonic®

## PT-L6600<sub>U/UL</sub> PT-L6500<sub>U/UL</sub>

3600 ANSI Lumens SXGA/XGA  
LCD Projectors

**BriteOptic™**  
Dual Lamp System

## Raising the Ceiling on Performance

- 1 BriteOptic™ Dual Lamp System with four brightness settings to choose from
- 2 Digital Cinema Reality for excellent moving images
- 3 Easy setup and maintenance: Auto setup with digital keystone correction



The difference is your image™



Center-mounted lens

# Centered on Quality

Panasonic's PT-L6600U/UL and PT-L6500U/UL LCD projectors incorporate our highly acclaimed BriteOptic™ Dual Lamp system, which delivers high-definition images with superb brightness.

Aided by extensive user input, we began by making key improvements to the system engine, then devised a symmetrical design that places the lens directly in the unit's center, for

easier image positioning. We also incorporated the latest DSP technology to assure precise, consistent performance.

The result: a series of projectors that deliver ultra-bright, beautiful images while greatly improving setup and maintenance ease.

See how brilliant your presentations look when delivered through Panasonic PT-L6600U/UL and PT-L6500U/UL projectors.



**BriteOptic™**  
Dual Lamp System

# Wide Variety: Choose the BriteOptic™ Projector that Best Meets Your Needs

## PT-L6600U



### SXGA Projector

- Ultrabright 3,600 ANSI lumens with 4-mode lamp operation
- BriteOptic™ technology and UHM™ lamps
- True SXGA (1,280 x 1,024), maximum UXGA (1,600 x 1,200) resolution
- Intelligent Image Resizing for VGA/SVGA/SXGA/Mac displays
- Multiple terminals, including digital video interface (DVI)
- Easy installation and maintenance
- Stackable for double brightness (up to 7,200 ANSI lumens)

## PT-L6500U



### XGA Projector

- Ultrabright 3,600 ANSI lumens with 4-mode lamp operation
- BriteOptic™ technology and UHM™ lamps
- True XGA (1,024 x 768), maximum UXGA (1,600 x 1,200) resolution
- Intelligent Image Resizing for VGA/SVGA/SXGA/Mac displays
- Multiple terminals, including digital video interface (DVI)
- Easy installation and maintenance
- Stackable for double brightness (up to 7,200 ANSI lumens)

## PT-L6600UL/L6500UL



The PT-L6600UL and PT-L6500UL deliver the same superior performance as the PT-L6600U and PT-L6500U, respectively, but come with no lens. Combine them with an optional lens to get the exact performance you need according to usage and operating conditions.

# A Host of Panasonic's Leading Technologies

## Ultrahigh Brightness and Contrast

Panasonic's advanced BriteOptic™ Dual Lamp System delivers both 3,600 ANSI lumens of brightness and superior color reproducibility. A corrective film is used to compensate for phase shifts in the light incident to the LCD panel, helping obtain a high contrast ratio. The result is reproduction of crisp, clear, super-bright images with outstanding depth.

## Increased Reliability

These projectors have a long lamp life of 3,000 hours (at dual lamp operation in standard mode). With the BriteOptic™ Dual Lamp System, even if one lamp burns out, the remaining lamp provides sufficient brightness.

## 4-Mode Lamp Operation

Switch the lamps to 3,600, 2,700, 1,800 or 1,350 ANSI lumens to achieve the desired brightness. The four settings let you place the priority on higher output, longer lamp life, or fail-safe operation to match your usage conditions.

## High Resolution & Intelligent Image Resizing

The PT-L6600U and PT-L6600UL offer true SXGA resolution and the PT-L6500U and PT-L6500UL provide true XGA resolution, allowing display of detailed computer graphics and text. When displaying images of other types, the signals are expanded or compressed through a digital processing system. This assures smooth outlines and outstanding picture definition with all types of images.



Terminals

## Flexible Connection

The PT-L6600U/UL and PT-L6500U/UL are equipped with a digital video interface (DVI), which lets you connect them with PCs for full digital image processing. You can also input signals from digital TV and DVD sources.

## Installation Options

Two ceiling mount brackets are available, one for high ceilings and one for lower ceilings. A stacking mount bracket and a simpler version are also available, for quick, easy, temporary stacking of two units.

## Easy Setup and Maintenance

The PT-L6600U/UL and PT-L6500U/UL feature a symmetrical design that places the



Lamps can be easily replaced.

lens right at the center, making it easier to position the projector and screen. Maintenance is easier too, thanks to a design that lets you replace a lamp without removing the projector from the bracket in either the ceiling-mounted or dual stacking configuration.

## A Wide Range of Uses

The PT-L6600U/UL and PT-L6500U/UL provide the quality and performance needed in almost any application. Use them in meeting rooms, theaters, museums, convention halls, public spaces, schools, research labs—anyplace where bright, beautiful images are a plus. Also, the superb resolution made possible by DVI input delivers images with exceptional detail and accuracy. This makes these projectors suitable for use as main systems for monitoring traffic or electric power, or in operation centers such as police, fire, air traffic control, and space development centers.

## One-Touch Auto Setup

This function automatically identifies the signal mode of the input source and adjusts the image accordingly. You get optimal viewing

## Options for More Flexible Installation

### ET-LE050

#### Fixed-focus short-throw lens

- Screen size: 40" to 60"
- Throw ratio: 0.7:1
- Throw distance: Approx. 0.55 m to 0.86 m



### ET-LE101

#### Short-throw lens

- Screen size: 30" to 200"
- Throw ratio: 1.3–1.8:1
- Throw distance: Approx. 1.1 m to 11.0 m



### ET-LE150

#### Short-throw lens

- Screen size: 30" to 300"
- Throw ratio: 1.8–2.4:1
- Throw distance: Approx. 1.4 m to 14.6 m



### ET-LE200

#### Medium-throw lens

- Screen size: 30" to 300"
- Throw ratio: 2.7–4.4:1
- Throw distance: Approx. 2.1 m to 26.7 m



### ET-LE300

#### Long-throw lens

- Screen size: 30" to 300"
- Throw ratio: 4.5–6.0:1
- Throw distance: Approx. 3.6 m to 35.4 m



### ET-PKL6500

#### Ceiling mount bracket for high ceilings



### ET-PKL6500S

#### Ceiling mount bracket for low ceilings



### ET-RMRC1

#### Wireless remote receiver

### ET-DFL6500

#### Dual stacking mount bracket for desk/ceiling mount

### ET-DFL6500P

#### Dual stacking mount bracket for desks

### ET-LAL6500

#### Replacement lamp unit

### ET-LAL6500W

#### Replacement lamp units (twin pack of ET-LAL6500 lamp units)

### ET-SCDV03

#### DVI cable (3 m)

quality, with no additional software, equipment or manual adjustment necessary.

**Lens Shift**

Shift the projected image vertically even after the projector is set in position. The PT-L6600U and PT-L6500U have a wide adjustment range, and the image remains distortion free.

This offers you the peace of mind that comes with the reliability of virtual-zero downtime.

**Other Valuable Features**


- Advanced shutter function: Minimizes distracting light leakage, as well as noise and power consumption, when the image is muted.
- Digital zoom: Portions of the image can be enlarged to 3x in steps of 0.1x.
- Freeze Frame: Moving pictures can be frozen at any time and projected as still pictures.
- Exhaust duct with noise cancel system achieves quiet 36-dB operation (with lamp power at Normal).
- LCD panels with micro lens array (MLA) for extra brightness (for the PT-L6600U/L6600UL only).
- Center-to-corner uniformity ratio (CCR) of over 90%
- Wireless remote with mouse control
- Lightweight and durable magnesium-alloy cabinet
- Power zoom/focus lens capable of projecting a 30° to 300° diagonal image
- Ceiling/desk, front/rear projection capable
- RS-232C computer interface and contact closure remote terminal
- S-Video compatibility
- Motorized retractable lens for lens protection
- Selectable 7-language on-screen menu (English, German, French, Spanish, Italian, Chinese, Japanese)
- Indicators for lamp errors, thermal warnings, and suggested replacement
- Universal AC power supply (auto-voltage: 100–120 V/220–240 V)
- Built-in stereo amplifier and speakers (3W + 3W) for true multimedia applications



Wireless remote control

**Projection setting example**

**L** : Projection distance when mounted with the ET-PKL6500. (Projection size is adjustable.)  
**H** : Height from upper/lower edge of projected image to center of lens.  
 (Position of projected image can be easily adjusted by using lens shift function.)



**PT-L6600U/L6500U**

Projection size	(W x H)	* inches: diagonally	L	H
40 inches	(813 x 610 mm)	1.4 – 1.9 m	(4'8" – 6'4")	0.030 – 0.30 m (1-3/16" – 11-13/16")
60 inches	(1,219 x 914 mm)	2.1 – 2.9 m	(6'11" – 9'8")	0.045 – 0.45 m (1-3/4" – 1'16")
100 inches	(2,032 x 1,524 mm)	3.6 – 4.8 m	(11'1" – 15'9")	0.076 – 0.76 m (2" – 2'6")
160 inches	(3,251 x 2,438 mm)	5.8 – 7.8 m	(19' – 25'7")	0.121 – 1.21 m (4-3/4" – 4')
220 inches	(4,470 x 3,353 mm)	8.1 – 10.7 m	(26'7" – 35'1")	0.167 – 1.67 m (6-9/16" – 5'6")
300 inches	(6,096 x 4,572 mm)	11.0 – 14.6 m	(36'1" – 47'11")	0.228 – 2.28 m (9" – 7'6")

**PT-L6600UL/L6500UL with the ET-LE050 fixed short-throw lens**

Projection size	(W x H)	* inches: diagonally	L	H
40 inches	(813 x 610 mm)	0.55 m	(1'10")	0.305 m (1')
50 inches	(1,016 x 762 mm)	0.70 m	(2'4")	0.381 m (1'3")
60 inches	(1,219 x 914 mm)	0.86 m	(2'10")	0.457 m (1'6")

**PT-L6600UL/L6500UL with the ET-LE101 short-throw lens**

Projection size	(W x H)	* inches: diagonally	L	H
40 inches	(813 x 610 mm)	1.1 – 1.4 m	(3'7" – 4'8")	0.030 – 0.30 m (1-3/16" – 11-13/16")
60 inches	(1,219 x 914 mm)	1.6 – 2.1 m	(5'2" – 7')	0.045 – 0.45 m (1-3/4" – 1'16")
100 inches	(2,032 x 1,524 mm)	2.7 – 3.6 m	(8'11" – 11'11")	0.076 – 0.76 m (2" – 2'6")
160 inches	(3,251 x 2,438 mm)	4.4 – 5.8 m	(14'5" – 19')	0.121 – 1.21 m (4-3/4" – 4')
220 inches	(4,470 x 3,353 mm)	6.1 – 8.1 m	(20' – 26'7")	0.167 – 1.67 m (6-9/16" – 5'6")
300 inches	(6,096 x 4,572 mm)	8.4 – 11.0 m	(27'7" – 36'1")	0.228 – 2.28 m (9" – 7'6")

**PT-L6600UL/L6500UL with the ET-LE150 short-throw lens**

Projection size	(W x H)	* inches: diagonally	L	H
40 inches	(813 x 610 mm)	1.4 – 1.9 m	(4'8" – 6'4")	0.030 – 0.30 m (1-3/16" – 11-13/16")
60 inches	(1,219 x 914 mm)	2.1 – 2.9 m	(6'11" – 9'8")	0.045 – 0.45 m (1-3/4" – 1'16")
100 inches	(2,032 x 1,524 mm)	3.6 – 4.8 m	(11'1" – 15'9")	0.076 – 0.76 m (2" – 2'6")
160 inches	(3,251 x 2,438 mm)	5.8 – 7.8 m	(19' – 25'7")	0.121 – 1.21 m (4-3/4" – 4')
220 inches	(4,470 x 3,353 mm)	8.1 – 10.7 m	(26'7" – 35'1")	0.167 – 1.67 m (6-9/16" – 5'6")
300 inches	(6,096 x 4,572 mm)	11.0 – 14.6 m	(36'1" – 47'11")	0.228 – 2.28 m (9" – 7'6")

**PT-L6600UL/L6500UL with the ET-LE200 medium-throw lens**

Projection size	(W x H)	* inches: diagonally	L	H
40 inches	(813 x 610 mm)	2.1 – 3.4 m	(6'11" – 11'2")	0.030 – 0.30 m (1-3/16" – 11-13/16")
60 inches	(1,219 x 914 mm)	3.1 – 5.2 m	(10'3" – 17')	0.045 – 0.45 m (1-3/4" – 1'16")
100 inches	(2,032 x 1,524 mm)	5.4 – 8.7 m	(17'9" – 28'7")	0.076 – 0.76 m (2" – 2'6")
160 inches	(3,251 x 2,438 mm)	8.6 – 14.1 m	(28'3" – 46.3')	0.121 – 1.21 m (4-3/4" – 4')
220 inches	(4,470 x 3,353 mm)	11.9 – 19.5 m	(39' – 64')	0.167 – 1.67 m (6-9/16" – 5'6")
300 inches	(6,096 x 4,572 mm)	16.3 – 26.7 m	(53'6" – 87'7")	0.228 – 2.28 m (9" – 7'6")

**PT-L6600UL/L6500UL with the ET-LE300 long-throw lens**

Projection size	(W x H)	* inches: diagonally	L	H
40 inches	(813 x 610 mm)	3.6 – 4.8 m	(11'10" – 15'9")	0.030 – 0.30 m (1-3/16" – 11-13/16")
60 inches	(1,219 x 914 mm)	5.4 – 7.1 m	(17'8" – 23'3")	0.045 – 0.45 m (1-3/4" – 1'16")
100 inches	(2,032 x 1,524 mm)	8.9 – 11.8 m	(29'2" – 38'8")	0.076 – 0.76 m (2" – 2'6")
160 inches	(3,251 x 2,438 mm)	14.3 – 18.9 m	((46'11" – 62')	0.121 – 1.21 m (4-3/4" – 4')
220 inches	(4,470 x 3,353 mm)	19.6 – 26.0 m	(64'4" – 85'4")	0.167 – 1.67 m (6-9/16" – 5'6")
300 inches	(6,096 x 4,572 mm)	26.7 – 35.4 m	(87'7" – 116')	0.228 – 2.28 m (9" – 7'6")



Front view

## Compatible graphic modes

VGA400	fh	fv	SXGA	fh	fv
640 x 400	24.8	56.4	1280 x 1024	52.4	50.0
	31.5	70.1		64.0	60.0
				72.4	66.3
VGA480	fh	fv		78.2	71.7
640 x 480	31.5	59.9		80.0	75.0
	35.0	66.7		<b>91.2</b>	<b>85.0</b>
	37.9	72.8			
	37.5	75.0	1280 x 1024i	46.2	86.0
	43.3	85.0		47.6	88.9
SVGA	fh	fv	UXGA	fh	fv
800 x 600	32.1	51.0	1600 x 1200	75.0	60.0
	35.2	56.3		87.5	70.0
	37.9	60.3		93.8	75.0
	48.1	72.1	Mac 16"	fh	fv
	46.9	75.0	832 x 624	49.7	74.6
	53.7	85.1	Mac 21"	fh	fv
XGA	fh	fv	1152 x 870	68.6	75.0
1024 x 768	48.4	60.0	NTSC	fh	fv
	56.5	70.1	768 x 480i	15.7	59.9
	60.0	75.0	PAL	fh	fv
	65.5	81.6	768 x 576i	15.6	50.0
	68.7	85.0			
	80.0	100.8	480p	fh	fv
	94.0	120.0	720 x 483	31.5	59.9
1024 x 768i	35.5	86.8	720p	fh	fv
MXGA	fh	fv	1280 x 720	45.0	60.0
1152 x 864	63.9	70.0	HDTV	fh	fv
	67.5	75.0	1920 x 1035i	33.8	60.0
	77.1	85.0			
1120 x 750	50.1	60.1			
1120 x 750i	32.6	80.0			

fh : Horizontal frequency (KHz)

fv : Vertical frequency (Hz)

*Italic: interlaced signals*

**Bold: For the PT-L6600U/L6600UL only**

### NOTE:

The display resolution of the PT-L6600U/L6600UL is 1366 x 1024 pixels. Input signals other than SXGA (1280 x 1024 pixels) will be converted to 1366 x 1024 pixels. When the input signal is SXGA (1280 x 1024 pixels), it will be projected as it is without being converted.

The display resolution of the PT-L6500U/L6500UL is 1024 x 768 pixels. If the display resolution indicated in the above data does not match this resolution, the input signal will be converted to 1024 x 768 pixels.



Control panel (Photo shows the PT-L6600U/L6500U. Controls of the PT-L6600UL/L6500UL are slightly different.)

## Specifications

	PT-L6600U	PT-L6500U	PT-L6600UL	PT-L6500UL
<b>Power supply:</b>	100–240 V AC, 50/60 Hz			
<b>Power consumption:</b>	600 W (during standby mode with fan stopped: Max. 10 W)			
<b>Max. amps:</b>	5.0 A			
<b>Color system:</b>	NTSC/M-NTSC/PAL/PAL-M/PAL-N/SECAM			
<b>LCD panel:</b>	1.3" (diagonal) with MLA	1.3" (diagonal)	1.3" (diagonal) with MLA	1.3" (diagonal)
<b>Display method:</b>	Transparent LCD panels (x 3)			
<b>Drive method:</b>	Active matrix			
<b>Pixels:</b>	1,398,784 (1,366 x 1,024) x 3	786,432 (1,024 x 768) x 3	1,398,784 (1,366 x 1,024) x 3	786,432 (1,024 x 768) x 3
<b>Pixel configuration:</b>	Stripe			
<b>Lens:</b>	Power zoom/focus lens (1:1–1:1.3) F 1.7–2.3, f 49.1–63.8 mm			(option) (option)
<b>Lamp:</b>	DC type 220 W UHM™ lamps (x 2)			
<b>Colors:</b>	Full color (16,777,216 colors)			
<b>Brightness:</b>	3600 ANSI lumens			
<b>CCR:</b>	90%			
<b>Contrast:</b>	400:1 (full field)	600:1 (full field)	400:1 (full field)	600:1 (full field)
<b>Resolution:</b>				
<b>RGB:</b>	1366 x 1024 pixels	1024 x 768 pixels	1366 x 1024 pixels	1024 x 768 pixels
<b>Video:</b>	1000 TV lines	760 TV lines	1000 TV lines	760 TV lines
<b>Screening frequency:</b>				
<b>S-Video/Video:</b>	Horizontal: 15.75/15.63 kHz, Vertical: 50/60 Hz			
<b>RGB:</b>	Horizontal: 24–97 kHz, Vertical: 50–120 Hz			
<b>Screen size:</b>	7.62–76.2 m (30–300 inches) diagonally (varies with optional lens)			
<b>Throw distance:</b>	1.4–14.6 m (4'8"–47'11") (varies with optional lens)			
<b>Optical axis shift:</b>	10/10–1/19			
<b>Installation:</b>	Ceiling/desk, front/rear (menu selection)			
<b>Built-in speakers:</b>				
<b>Size:</b>	7 x 4 cm (2-3/4" x 1-9/16") (x 2)			
<b>Output power:</b>	6 W (3 W + 3 W) (10% THD)			
<b>On-screen display languages:</b>	English, German, French, Spanish, Italian, Chinese, Japanese			
<b>Terminals:</b>				
<b>RGB/YUV in:</b>	D-sub HD 15-pin x 1, 5 BNC x 1			
<b>RGB out:</b>	D-sub HD 15-pin x 1			
<b>Digital RGB in:</b>	DVI-D 24-pin x 1			
<b>Digital RGB out:</b>	DVI-D 24-pin x 1			
<b>S-Video in:</b>	Mini DIN 4-pin x 1			
<b>Video in:</b>	BNC x 1			
<b>Video out:</b>	BNC x 1			
<b>Video audio in:</b>	RCA jack (L, R) x 1			
<b>RGB audio in:</b>	M3 (L, R) x 1			
<b>Audio monitor out:</b>	M3 (L, R) x 1			
<b>RS-232C in:</b>	D-sub 9-pin x 1			
<b>RS-232C out:</b>	D-sub 9-pin x 1			
<b>Contact closure:</b>	D-sub 9-pin x 1			
<b>USB in:</b>	Type B x 1 (up, for mouse)			
<b>USB out:</b>	Type A x 1 (down, for USB hub)			
<b>Wired remote in:</b>	M3 x 1			
<b>Wired remote out:</b>	M3 x 1			
<b>Noise level:</b>	36 dB (at standard mode)			
<b>Dimensions</b>				
<b>(W x H x D):</b>	495 x 179 x 495 mm (19-15/32" x 7-1/16" x 19-15/32")			
<b>Weights:</b>	13.8 kg (30.5 lbs.)		12.6 kg (27.8 lbs.)	
<b>Operating temperature:</b>	0°–40°C (32°–104°F)			
<b>Operating humidity:</b>	20%–80% (no condensation)			
<b>Safety regulations:</b>	UL1950, C-UL, FCC			
<b>Remote control unit</b>				
<b>Power supply:</b>	3 V DC (AA-size battery x 2)			
<b>Operation range:</b>	Approx. 7 m (23') when operated from directly in front of the signal receptor			
<b>Weight:</b>	Approx. 102 g (0.225 lb.) (including batteries)			
<b>Dimensions (W x H x D):</b>	46 x 34 x 190 mm (1-13/16" x 1-11/32" x 7-15/32")			
<b>Supplied accessories:</b>	Wireless/wired remote control unit, Cable for remote control unit (15 m), Remote control adapter plug, Batteries for remote control unit, Power cord, VGA cable, USB cable, Exhaust guide			
<b>Optional accessories:</b>	Replacement lamp unit: ET-LAL6500 (single lamp), ET-LAL6500W (set of two lamps) Ceiling mount bracket: ET-PKL6500 (for high ceilings), ET-PKL6500S (for low ceilings) Fixed-focus short-throw lens: ET-LE050, Short-throw lens: ET-LE101, Short-throw lens: ET-LE150, Medium-throw lens: ET-LE200, Long-throw lens: ET-LE300, Dual stacking mount bracket: ET-DFL6500 (for desk/ceiling mount), Dual stacking mount bracket: ET-DFL6500P (for desk mount), DVI cable: ET-SCDV03, Wireless remote receiver: ET-RMRC1			

# Panasonic

Panasonic is the brandname of Matsushita Electric.

Panasonic Broadcast & Television Systems Company  
Presentation Systems Group  
(800) 528-8601  
www.panasonic.com/projectors

**Headquarters**  
1 Panasonic Way, 4E-7  
Secaucus, NJ 07094  
(201) 348-7621

**Canada**  
**Panasonic Canada Inc.**  
5770 Ambler Drive  
Mississauga, Ontario  
Canada L4W 2T3  
(416) 624-5010

Weights and dimensions shown are approximate. Specifications subject to change without notice. This product may be subject to export control regulations. UHM is a trademark of Matsushita Electric Industrial Co., Ltd. PS/2, VGA and XGA are trademarks of International Business Machines Corporation. Macintosh is a registered trademark of Apple Computer, Inc. SVGA is a registered trademark of the Video Electronics Standards Association. Windows is a registered trademark of Microsoft Corporation. All other trademarks are the property of their respective trademark owners. Projection images simulated.

PT-L6600/L6500U1-02JUN20K Printed in Japan.