PLEASE READ

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

ABOUT PROJECTOR.COM

Projector.com (http://www.projector.com) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.



Audio L/R, for S Video PC Audio In USB Audio, L/R for Video RGB, PC or Control S-Video Component, In by PC Composite Video Audio Out Monitor,

Out



Portable Powerful LCD Projector

- 1800 lumen brightness
- SVGA resolution
- Easy to transport, only 6.6 lbs.
- Full set of features, 3 inputs
- Monitor loopthrough
- Switched audio output
- Automatic keystone correction
- Wide angle zoom lens





ImagePro 8054 **Premium-quality LCD projector**

A new way of thinking about projection.

The Dukane ImagePro 8054 is a projector that can be easily moved around while still providing higher image brightness and features that make presentations easy. It is simple to use, transport, and can be setup in a minute.

This full-featured LCD projector is ideal for classrooms, conference rooms or other locations where a bright image is required. Use it as a portable or mount it on the ceiling.

Key features:

- SVGA (800 x 600) resolution
- 1800 ANSI Lumens of brightness
- Vibrant rich colored images
- Easy carry 6.6 lbs.
- Flexibility with 1 computer and 2 video inputs
- Full function remote with mouse/cursor control
- Audio output switches with selection of either video or computer source
- Wide angle zoom lens permits closer placement to the screen
- HDTV Compatible
- "Silent Running" so you hear only your message
- Automatic vertical keystone correction
- Two year warranty and One year Peace -of- Mind service

8054 Image Size Distance Table

Image Size 4:3		Throw Distance		
Diagonal	Width	Min.	Max.	a*
Inches	Inches	Feet	Feet	Inches
40	32	3.9	4.7	2.3
60	48	5.9	7.1	3.5
100	80	10.0	12.0	5.8
120	96	12.0	14.4	7.0
150	120	15.1	18.1	8.7
210	168	21.1	25.3	12.2
300	240	30.2	36.3	17.4

a* = Distance Below Lens Center line.

Dukane Corporation Audio Visual Products Division 2900 Dukane Drive St. Charles, Illinois 60174 800-676-2485 or 2486 630-584-5156

toll-free fax e-mail

avsales@dukcorp.com www.dukcorp/av.com

ImagePro is a registered trademark of Dukane Corporation #11630-D-04

Specifications

Image Element 0.7" polysilicon TFT x3, MLA Brightness

1800 ANSI lumens

(1500 lumens in Whisper Mode) 800 x 600 pixels (H X V), SVGA

Contrast 400 to 1 fh 15-100 kHz, fv 50-120 Hz

Scanning Frequency

Resolution

Lens Throw Ratio

Manual zoom f21.6 to 25.9mm, 1.2X 1.5 -1.8 to 1 throw distance

to image width

Digital, vertical +/-30 deg, Automatic Keystone Correction

4:3, 16:9 compatible Aspect Ratio Computer VGA, SVGA, XGA, SXGA,

Compatibility UXGA Compressed, Mac 13" & 16" Video Compatibility NTSC, NTSC 4.43, PAL, PAL-M,

PAL-N, PAL60, SECAM,

HDTV 1080i,1080i/50 Hz, 720p,

575i, 480p

Component Video, Horizontal res, 800TV line Image Control Freeze function, electronic magnification and pan

Mouse Control Using USB Front/rear/ceiling Projection Modes Color Reproduction 24 bit (16.7 million)

Lamp 205 W, NSH,

(164W Whisper Mode) Lamp Life 2000 hours (typical), 3000 (Whisper Mode) Audio 1 speaker, 1 watt

Throw Distance 29" to 435" 21" to 300" Screen Size, diagonal

Inputs, Video (1) Component, D-sub 15 pin, shared

(1) Min DIN 4-pin, S-video, (1) RCA, composite video (1) Audio, Stereo, RCA x 2, for

C-video

(1) Audio, Stereo, RCA x 2, for S-video

Inputs, Computer (1) Signal: D-sub, 15 pin, shared Audio, Stereo mini jack for PC

Outputs, Monitor 15 pin, D-sub, RS-232

Outputs, Control PC control DIN 8 pin, RS-232 Audio out, Stereo mini jack USB Type B, mouse control

Kensington slot Security

37dB standard, 32dB in Whisper Mode Fan Level

Operating Temperature 32 to 95 deg. F (0-35 deg C) AC 100-120V, AC 220-240V Power

50/60 Hz, 270 watt, Std. consumption

Size (WxHxD) 12.2" x 3.5" x9.1"

Weight 6.6 lbs. 12.6 lbs. Shipping Weight

14.7" x 11" x 17.3" Carton Size

Accessories Included Remote control, RGB cables, RCA

video/audio cable, power cord, USB cable, operator's manual, soft

carry case

Safety UL/CUL, FCC Class B Optional Accessories Lamp 456-8766

Rolling briefcase; 185-406,

Ceiling mount, universal PJF-UNV-S

Two (2) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply).Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

PLEASE READ

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

ABOUT PROJECTOR.COM

Projector.com (http://www.projector.com) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.