PLEASE READ

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

ABOUT PROJECTOR.COM

Projector.com (http://www.projector.com) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.



Computer M1-DA Audio RS232 Computer In (R) RGB, In Audio **RJ-45** S-Video Out Network IR Sensor Kingston Lock Slot Power Computer Monitor Audio Out Computer Audio Out Video In In (L)

- Business
- Education



ImagePro 8758 Data/Video projector

- Network Connection, RJ-45
- XGA resolution
- 2200 lumens brightness
- HDTV compatible
- Digital keystone correction, Horizontal & Vertical
- Very quiet operation
- LCD with status Information



View the status of your projector via the LCD window on top of the unit.



ImagePro 8758 Portable LCD projector

A way to present your images anywhere

The Dukane ImagePro 8758™ offers best-in-class capabilities with intuitive controls. Get outstanding color saturation and brightness that lasts. Use the network connection to set up any meeting room by remote monitoring and control.

The high-end features mean that you do less work. Automatic horizontal and vertical keystone correction,

plus ceiling detection ensure your image is proper, with no work on your part. Automatic synchronization with computer and video sources allows for quick and smooth transitions.



Key features:

- Light weight
- 2200 lumens brightness
- XGA resolution
- Simple, icon based menu
- HDTV compatible
- Zoom lens
- Automatic ceiling detection
- Network connection
- Picture-In-Picture (PIP)
- LCD window with status information

8758 Image Size Distance Table

Image Size 4:3		Throw Distance		
Diagonal	Width	Min.	Max.	a*
Inches	Inches	Feet	Feet	Inches
40	32	4.3	5.1	1.5
60	48	6.4	7.6	2.0
100	80	10.7	12.7	4.0
120	96	12.9	15.3	5.0
150	120	16.1	19.1	6.5
210	168	22.5	26.7	7.0

a* = Distance Below Lens Center line.

<u>DUKANE</u>

Audio Visual Products 2900 Dukane Drive St. Charles, Illinois 60174 www.dukcorp.com/av



Toll-free: 800-676-2485 | Fax: 630-584-5156 E-mail: avsales@dukcorp.com

Specifications 8758

Image Element 0.8" polysilicon TFT x3, MLA

Brightness 2200 ANSI lumens

Resolution 1024 x 768 pixels (H X V), XGA

Contrast 400 to 1

Scanning Frequency fh 16-110 kHz, fv 50-85 Hz

Lens Manual zoom, 1.2X

Lens Throw Ratio 1.61 - 1.91 to 1 throw distance

to image width

Keystone Correction Digital, vertical +/-25 deg,

Horizontal +/-15 deg
Computer SVGA, VGA, XGA, and
Compatibility SXGA Compressed,
Mac 13" and Mac 16"

Video Compatibility NTSC, NTSC 4.43, PAL, PAL-M,

PAL-N, PAL60, SECAM, HDTV,

1080i,1080i/50 Hz, 720p, 480i/p

Image Control Freeze function, electronic magnification and pan

Mouse Control
Picture in Picture, PiP
Other Feature
Projection Modes
Color Reproduction

Using USB – using M1-USB
Yes, video in computer
Mask reveal for images
Front/rear/ceiling
24 bit (16.7 million)

Lamp 170 W UHP
Lamp Life 2000 hours
Audio 2 speaker, 2 watt
Throw Distance 60" to 400"
Screen Size, diag. 40" to 300"

Inputs, Video Component, via adapter for M1-D/A

S-video, Min DIN 4-pin, Composite video, RCA x 1

Audio, Stereo, RCA x 2, for c-video Inputs, Computer 1 x RGB Signal: D-sub, 15 pin

Computer, Stereo Mini Audio x 1

M1-D/A Computer (DVI)

Outputs Monitor 15 pin, D-sub

Outputs, Control

15 pin D-Sub, RS-232

Audio out, Stereo mini jack
USB, mouse control w M1-D/A

Network connection RJ-45 port Security Kensington slot

Fan Level Ultra quiet, 34 dB normal

Operating Temp. 50 to 95 deg. F

Power AC 100-240V, AC 50/60 Hz, 260 watt

Size (WxHxD) 11.6" x 4.1" x 10.3"

Weight 7.5 lbs. Shipping Weight 14 lbs.

Carton Size 16" x 16" x 14"

Accessories Included Remote control, batteries, power

cord, M1-D/A computer and USB cable,

3.5 mm audio cable, RCA x 3 cable, operators manual and

soft carry case

Safety UL/CUL, FCC/DOC Class A,

Optional Accessories Lamp; 456-8758

Rolling briefcase; 185-406, Ceiling mount, universal; PJF-UNV-S M1 to Component adapter; SP-M1-ADPT

Two (2) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply). Includes Dukane's FREE 1 year *Peace-of-Mind Loaner Program*.

PLEASE READ

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

ABOUT PROJECTOR.COM

Projector.com (http://www.projector.com) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.