PLEASE READ

This manual is provided as a free service by Projector.com.


We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

ABOUT PROJECTOR.COM

Projector.com (<u>http://www.projector.com</u>) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.





- 1800 lumen brightness
- XGA resolution
- Easy to transport, only 6 lbs.
- Full set of features, 3 inputs
- Monitor loopthrough
- Switched audio output
- Automatic keystone correction
- Wide angle zoom lens







ImagePro 8766 **Quality XGA LCD projector**

The Dukane ImagePro 8766 is a projector that can be easily moved around while still providing higher image brightness and features to make your class or presentation easy. It is simple to use, transport, and can be setup in a minute.

This full-featured LCD projector is ideal for classrooms, conference rooms or other locations where a bright image is required. Use it as a portable or mount it on the ceiling.



Key features:

- True XGA (1024 x 768) resolution
- 1800 ANSI Lumens of brightness
- Vibrant rich colored images
- Easy carry 6 lbs.
- Flexibility with 1 computer and 2 video inputs
- Full function remote with mouse/cursor control
- Audio output switches with selection of either video or computer source
- Wide angle zoom lens permits closer placement to the screen
- "Silent Running" so you hear only your message
- Automatic vertical keystone correction
- Peace of Mind Service

8766 Image Size Distance Table

Image Size 4:3		Throw Distance		
Diagonal	Width	Min.	Max.	a*
Inches	Inches	Feet	Feet	Inches
40	32	3.9	4.7	2.3
60	48	5.9	7.1	3.5
100	80	10.0	12.0	5.8
120	96	12.0	14.4	7.0
150	120	15.1	18.1	8.7
210	168	21.1	25.3	12.2
300	240	30.2	36.3	17.4

a* = Distance Below Lens Center line.



Dukane Corporation Audio Visual Products Division 2900 Dukane Drive St. Charles, Illinois 60174 800-676-2485 or 2486 630-584-5156 avsales@dukcorp.com www.dukcorp/av.com

toll-free fax e-mail

ImagePro is a registered trademark of Dukane Corporation #11622-B-04

Specifications

0.7" polysilicon TFT x3, MLA

(1400 lumens in Whisper Mode)

1024 x 768 pixels (H X V), XGA

Manual zoom f 21.6 to 25.9mm, 1.2X

Digital, vertical +/-30 deg, Automatic

4:3, 16:9, with 4 modes selectable

fh 15-100 kHz, fv 50-120 Hz

1.5 -1.8 to 1 throw distance

SVGA, VGA, XGA, and

Mac 13" and Mac 16"

PAL-N, PAL60, SECAM,

Horizontal res, 800TV line

Freeze function, electronic

magnification and pan

24 bit (16.7 million)

1 speaker , 1 watt

S-video, Min DIN 4-pin,

Composite video, RCA x 1

29" to 432"

21" to 300"

15 pin, D-sub

Ultra quiet

SXGA/UXGA Compressed,

NTSC, NTSC 4.43, PAL, PAL-M,

HDTV 1080i,1080i/50 Hz, 720p,

205 W, 160W in whisper mode

Component, D-sub 15 pin, shared

Audio, Stereo, RCA x 2, for C-video

Audio, Stereo, RCA x 2, for S-video RGB Signal: D-sub, 15 pin, shared

Audio, Stereo mini jack for PC

PC control DIN 8 pin, RS-232

Kensington slot and code word

Audio out, Stereo mini jack USB Type B, mouse control

27dB in Whisper Mode

2000 hours, 3000 in whisper mode

1800 ANSI lumens

400 to 1

to image width

576p, 480i/p

Using USB Front/rear/ceiling

Image Element Brightness Resolution

Contrast Scanning Frequency Lens Lens Throw Ratio

Keystone Correction Aspect Ratio Computer Compatibility

Video Compatibility

Component Video, Image Control

Mouse Control Projection Modes Color Reproduction Lamp Lamp Life Audio Throw Distance Screen Size, diagonal Inputs, Video

Inputs, Computer

Outputs Monitor Outputs,Control

Security

Fan Level

Safety

Operating Temperature 32 to 95 deg. F (0-35 deg C) AC 90-120V, AC 220-240V Power 50/60 Hz, 260 watt, 7.5W standby 12.2" x 3.5" x9.1" Size (WxHxD) Weight 6.5 lbs. Shipping Weight 12.6 lbs. Carton Size

14.7" x 11" x 17.3" Accessories Included Remote control, batteries, power cord, Computer cable, USB cable, operator's manual and soft carry case. UL/CSA, FCC/DOC Class B, CE Lamp 456-8766 Optional Accessories Rolling briefcase; 185-406, Ceiling mount, universal; PJF-UNV-S

Two (2) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply).Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.



PLEASE READ

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

ABOUT PROJECTOR.COM

Projector.com (<u>http://www.projector.com</u>) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.