

## **PLEASE READ**

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

## **ABOUT PROJECTOR.COM**


Projector.com (<http://www.projector.com>) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.



## ImagePro 8915 Portable LCD Projector

- 3200 lumen brightness
- XGA resolution
- 400:1 contrast ratio
- Four 3 watt speakers
- Auto vertical keystone correction
- Remote with laser pointer
- Network capability (RJ45)




# 8915 **DUKANE**

# ImagePro 8915

## Premium-quality LCD projector

The Dukane ImagePro 8915 is a powerful yet versatile LCD projector designed to open new possibilities in multimedia projection. Bright enough for most large classrooms and conference rooms, the 8915 is sure to impress with realistic colors, sharp contrast, and brilliant images.

Save money with the 8915 by eliminating the need for additional external speakers. By incorporating four built-in 3W speakers, which is typically sufficient for most classrooms, you can be sure your message is heard. In addition, full connectivity and networking capabilities make this one of the most versatile and efficient projectors available today.



### Key features:

- 3200 lumens brightness
- XGA (1024 x 768) resolution
- 400:1 contrast ratio
- Vibrant rich colored images
- Four 3 watt speakers
- Automatic vertical keystone correction
- Remote with laser pointer
- HDTV compatible
- Five Year Warranty and One Year Peace of Mind Service

### 8915 Projection Table

Image Size 4:3		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
40	32	3.9	4.8
60	48	5.9	7.2
80	64	8.0	9.6
100	80	10.0	12.0
120	96	12.0	14.5
150	120	15.1	18.1
200	160	20.1	24.3
250	200	25.2	30.3
300	240	30.3	36.4

Throw Ratio (distance to width) 1.50 1.80

# DUKANE



Audiovisual Products  
2900 Dukane Drive  
St. Charles, Illinois 60174  
www.dukcorp.com/av

Toll-free: 800-676-2485  
Fax: 630-584-5156  
E-mail: avsales@dukcorp.com

### Specifications

Image Element	0.8" polysilicon TFT x3, MLA
Brightness	3200 ANSI lumens 2600 (whisper mode)
Resolution	1024 x 768 pixels (H X V), XGA
Contrast	400:1
Scanning Frequency	fh 15-91 kHz, fv 50-120 Hz
Lens	Manual zoom (F=1.7 to 2.1), 1.2X
Lens Throw Ratio	1.5 -1.8 :1 throw distance to image width
Keystone Correction	Digital, vertical +/-15 deg, automatic horizontal +/- 5 deg
Aspect Ratio	4:3, 16:9, selectable
Computer Compatibility	SVGA, VGA, XGA, and SXGA Compressed, MAC16"
Video Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, HDTV 1080i, 720p, 575i, 480i/p
Image Control	Freeze function, electronic magnification and pan
Mouse Control	Using USB
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	230W UHB
Lamp Life	2000 hours
Audio	3.0 W x 4
Throw Distance	46" to 364"
Screen Size, diagonal	40" to 500"
Inputs, Video	(1) Component, RCA x 3 (1) S-video, Min DIN 4-pin, (1) Composite video, RCA x 1
Inputs, Computer	Audio, Stereo, RCA x 2, (L/R) (2) RGB Signal: D-sub, 15 pin (1) DVI (digital RGB)
Outputs Monitor	Audio, Stereo mini jack x 1 15 pin, D-sub
Outputs Audio	Audio, Stereo mini jack x 1
Outputs, Control	9 pin D-sub Connector, RS232C USB connector x 1 3.5mm mini jack (wired remote control)
Network	RJ-45 port / 10Base-T
Security	Kensington slot
Fan Level	38dB, (33dB in whisper mode)
Operating Temperature	32 to 95 deg. F (0-35 deg C)
Power	AC 100-120V, AC220-240V 50/60 Hz, 370 watt
Size (WxHxD)	13.2" x 3.7" x 10.4"
Weight	8.6 lbs.
Carton Size	14.3" x 16" x 17.3
Shipping Weight	20.2 lbs.
Accessories Included	Remote control w/ laser pointer, batteries, power cord, RGB Cable, filter cover, operator/safety manual, soft case.
Safety	UL, C-UL, FCC Class B, CE, TUV
Optional Accessories	Lamp 456-8915 Rolling briefcase; 185-406, Ceiling mount , universal; PJF-UNV-S

### Two (5) year limited warranty

on parts and labor in North America, lamp excluded (for other locations, local warranties apply).

Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

# 5YR

## **PLEASE READ**

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

## **ABOUT PROJECTOR.COM**

Projector.com (<http://www.projector.com>) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.