

# SHARP®



The "ultra" of "ultra-portables".

Sharp's new **Notevision M15X** (PG-M15X) is among the smallest, lightest, and highest performing projectors in the Compact/Mobile category! This "micro-mobile" size projector weighs just over **3 pounds**, and in spite of its amazingly compact size and weight, provides a full **1100 ANSI Lumens** brightness!

It boasts built-in computer and video inputs, audio systems, automatic image setup and digital keystone correction. This model additionally includes a USB-PS/2 wireless remote - with mouse control - for total presentation flexibility from anywhere in the room.

Choose the **Notevision M15X** (PG-M15X) for high-end "XGA" resolution, providing a full 1024 x 768 native resolution, with Intelligent Resizing up to SXGA resolution (1280 x 1024 pixels) .

It even comes standard, at no charge, with Sharp ER - our industry leading parts and labor warranty with 24 hour emergency repair or replace service to ensure maximum reliability. The **Notevision M15X** comes housed in a durable magnesium alloy enclosure.

**Notevision M15X.** Ultra features for ultra presentations in an ultra small package!

### ADVANCED FEATURES

- \* 1100 ANSI Lumen Brightness
- \* Data Input for PC or Mac
- \* International Power Supply (110-240V AC)
- \* Wireless Remote with Mouse Control
- \* Digital Keystone Correction up to +/-19°
- \* Designed to Fit Under-Seat on an Airplane Complete w/Notebook PC
- \* Component Video Input (480i) for Displaying DVD and DTV Sources
- \* 1.2:1 Manual Zoom/Focus Lens

### PROJECTION DISTANCES

Screen Diagonal	Screen Width	Screen Height	Minimum Distance	Maximum Distance
40"	32"	24"	5'4"	6'5"
60"	48"	36"	8'0"	9'7"
72"	58"	43"	9'7"	11'6"
84"	67"	50"	11'2"	13'5"
100"	80"	60"	13'4"	16'0"
150"	120"	90"	20'0"	24'0"
200"	160"	120"	26'8"	32'0"
250"	200"	150"	33'4"	40'0"

APPROX. PROJECTION DISTANCE FROM SCREEN TO FRONT OF LENS

Distributed by:

### SPECIFICATIONS

Resolution	PG-M15X - Native XGA (1024 x 768) up to SXGA (1280 x 1024)
TV Lines	580 TV Lines
Panel Type	0.7" DMD™
H & V Frequency	fh 31.5 - 80 kHz /fv 56 - 85 Hz
Dot Clock	25 - 135 MHz
Compatibility	PC & Mac
Video System	NTSC/PAL/PAL-N/PAL-M/SECAMM/NTSC 4.43
Resizing	Image ACE Resizing
Brightness	1100 ANSI Lumens w/ 80% CCR
Contrast Ratio	500:1
Lens Type	1.2:1 Manual Zoom/Focus
Aspect Ratio	4:3 & 16:9
Remote Control	IR W/Mouse Control
IR Carrier Frequency	38kHz
Audio System	2.0 Watt Monaural
Lamp	200 Watt, DC User-replaceable
Lamp Part No.	BQC-PGM15X/1
Fan Noise	38 dB
Power Source	110-240 VAC AC, 50/60Hz
Power Consumption	180 Watts
Heat Dissipation	<680 BTU/hour
Dimensions	8.9" (W) x 2.0" (H) x 6.9" (D) (Main Body Only) 8.9" (W) x 2.6" (H) x 6.9" (D) (Includes Feet)
Weight	3.5 lbs.
Limited Warranty	3 Years Parts/Labor & 2 Years Sharp Express Repair, Lamp 90 Days

### INPUTS/OUTPUTS

- \* 29-pin DVI-D (computer input)
- \* Separate Video Input [Composite (RCA) and S-Video (4 pin DIN)]
- \* Audio Input (3.5mm Stereo Minijack)
- \* RS-232C
- \* Component Input (shared with computer input)
- \* 15-pin mini D-sub (computer output)

### INCLUDED ACCESSORIES

Wireless Remote Control, Two AAA Size Batteries, 6' Power Cord, 6' Computer RGB Cable, 6' Audio Cable, Audio Adapter (3.5mm stereo to RCA), USB Mouse Control Cable, PS/2 6' Mouse Control Cable, 6' Video Cable, 6' S-Video Cable, 6' RS-232 Conversion Cable (7 pin DIN to 9 pin HD male adapter), 6' DVI to 15 pin HD cable, DVI/15 pin HD Adapter, Soft Pouch, Projector Operation Manual, Projector Quick Reference Guide

### OPTIONAL ACCESSORIES

- AN-M100PCBAG** Soft Sided Carry-on Bag (Projector & PC)
- AN-M100CC** Hard Shell Carrying Case (Projector only)
- AN-M100SC** "ATA" Style Shipping Case for Projector
- AN-M100WB** Wheeled "Tilt-N-Go" Bag for Projector & PC
- AN-C200BAG** Soft Sided Carry-on Bag
- AN-PGCM85** Ceiling bracket for PG-M15X

Design and specifications are subject to change without notice. All trademarks are property of their respective holders.

SHARP ELECTRONICS CORPORATION  
LCD Products Group, Sharp Plaza, Mahwah, NJ 07430-2135  
Sales "Hotline" (201) 529-8731 / Fax Number (201) 529-9636  
Corporate Headquarters (201) 529-8200 / Literature Faxback (630) 378-9987  
E-mail: ProLCD@SharpSEC.com  
[www.SharpLCD.com](http://www.SharpLCD.com) • 1-888- GO SHARP

