

**Exceptional LCD performance**

High brightness, superior contrast and super-fast 16 ms video response time combine to deliver crisp, clear text and smooth motion images for video applications.

WEGA Engine™ system

Intelligent digital processing system delivers superb picture quality by minimizing signal deterioration caused by digital-to-analog conversion.

Cost of Ownership

Burn-in resistant LCD technology ensures long life when using static images. Low power consumption and long-life panel delivers hours of use to keep your total cost of ownership low.

Upscale style

Scratch-resistant crystal-look bezel in a choice of three elegant colors including pearl white adds upscale refinement to any interior. Cable management system conceals wires and cables, keeping the back looking streamlined and uncluttered.

Networking options

Optional network cards and boxes (sold separately) let you centrally control, deliver and troubleshoot digital content across a standard IP network to one or hundreds of networked displays. Reduce labor and production costs associated with managing individual content.

Sony Large Panel LCD Displays incorporate WEGA Engine™ technology to deliver remarkable resolution and image clarity. Fast video response time ensures crisp streaming video. Flexible networking options let you centrally control digital content across to hundreds of networked displays. Crystal-look bezel and clean rear panel with cable management system adds upscale refinement to any interior.

FWD-32LX1

Display



LIKE NO OTHER™

Model
FWD-32LX1

Model Number
FWD-32LX1/B (Black), FWD-32LX1/S (Cool Silver), FWD-32LX1/W (Pearl White)

Screen Size
32"

Resolution
WXGA 1366 x 768

Pixel Pitch
.51 x .51 mm

Color
16.7 million

Panel Type
a-Si-TFT active matrix LCD panel

Screen Protector
Anti-Glare/Anti-Reflective

Color Systems
NTSC, PAL, SECAM, NTSC4.43, PAL60, PAL-M, PAL-N

Audio
14W Stereo AMP (7W x 2 Digital AMP)

Video Inputs
RGB/Component (HD-15), DVI-D HDCP, Composite (BNC), YUV (Composite)

Picture Modes
Custom (3), Vivid, Standard

Color Temperature Control
Discrete Control RGB

Remote Control
RS232C and Multi-Function Remote

Closed Caption Decoder
Yes

Weight
38.5 lbs.

Dimensions (W x H x D)
31.6 x 19.4 x 4.2

Power Consumption
170 watts (typical)

Design Color
Black, Cool Silver and Pearl White

On-Screen Control
Yes

Safety Regulations
UL1950, CSA No.950 (c-UL), CE LVD (EN60950), FCC Class B, VCCI Class B, CE EMC (EN55022 Class B, EN61000-3-2, EN61000-3-3), C-Tick (AS/NZS 3548/95, AS/NZS 4252.1), CCIB, JEIDA, CB, KTL, MIC

Limited Warranty
2 years parts and labor, 1 year panel

Extended Warranty
Optional Plans for up to 5 years on-site, or 3 years depot service

Picture and Picture
Picture in Picture
Size (H x W x D)
31.6 x 19.4 x 4.2

Weight
38.5 lbs

Supplied Accessories
DVI-D Cable, AC Power Cord, Operating Instructions, AC Plug Holder (2), AA/R6 Size Battery (2), Cable Holder (4), Remote Control

Optional Accessories
Networking: NSP-1 (Digital Signage Player), NSP-100 (Network Video Player), EBS-N200 (Status Control and Streaming realtime video sent over IP with connectivity to PJNet), BKM-FW32 (Internal Network Management Device for status and control over IP), ICS-SP20 (TV

Tuner and Hospitality System)
Mounting Solutions: PLP91/D (Tilt Wall Bracket), SPM-TRI/C (Table Top Stand)
Input Boards: BKM-FW11 (Component/RGB Input Adapter), BKM-FW12 (RGB Component Loop Through)
Speakers: SS-SP32FW/S (Speakers for Black and Silver models), SS-SP32FW/W (Speakers for White Model)
Software: PJNet (Asset Management tool to control up to 255 Sony Plasmas or Projectors), DCDS (Asset Management tool to schedule and control up to 10,000 points)

©2004 Sony Electronics Inc. All rights reserved. Features and specifications are subject to change without notice. All trademarks referenced herein are trademarks of Sony or their respective owners.

SONY®